

INTERNATIONAL
STANDARD

ISO/IEC
9318-2

First edition
1990-12-15

**Information technology — Intelligent Peripheral
Interface**

Part 2:

Device specific command set for magnetic disk drives

*Technologies de l'information — Interface pour les périphériques intelligents —
Partie 2: Jeu de commandes spécifiques appareil pour les unités disques
magnétiques*



Reference number
ISO/IEC 9318-2 : 1990 (E)

Contents

	Page
1 Scope	1
2 Normative references	3
3 Definitions and conventions	4
3.1 Definitions	4
3.2 Conventions	5
4 General description	6
4.1 Application environment	6
4.2 Logical Interface characteristics	6
4.2.1 Slave Control	6
4.2.2 Information transfer	6
4.2.3 Data transfers	6
4.2.4 Format Control	6
4.3 Responsibility	6
4.3.1 Master	6
4.3.2 Slave	7
5 Physical Interface Considerations	7
5.1 Information transfer	7
5.1.1 Octet Mode	7
5.1.2 Transfer Mode	7
5.1.3 Termination of transfers	7
5.1.4 Data streaming	7
5.2 Bus Octets	8
5.2.1 Unsupported Bus Octets	8
5.2.2 Bus Control Octet	8
5.2.3 Master Status Octet	8
5.2.4 Slave Status Octet	9
5.2.5 Request Interrupts Octet	9
5.2.5.1 Types of Interrupts	9
5.2.5.1.1 Class 1 Command Completion Interrupt	9
5.2.5.1.2 Class 2 RPS Interrupt	10
5.2.5.1.3 Class 3 Status Pending Interrupt	10
5.2.6 Address Octet Response	10
5.2.7 Selective Reset Octet	10
5.2.8 Selection Octet	11
5.2.9 Request Transfer Settings Octet	11
5.2.10 Slave Transfer Settings Octet	11
5.2.11 Request Slave Interrupts Octet	11
5.2.12 Slave Interrupts Octet	12
5.3 ATTENTION IN signal	12
6 Slave Functions	13
6.1 Disk Format	13
6.1.1 Format 1 – Fixed Block Format	13
6.1.1.1 Fixed Block Hard Sector	13
6.1.1.2 Fixed Block Soft Sector	13
6.1.2 Format 2 – Variable Block Format	13
6.1.3 Format Control	13

© ISO/IEC 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

6.2	Format Specification	14
6.2.1	Format initialization	14
6.2.2	Manufacturer's Format Specification	14
6.2.3	Fixed Block mode	15
6.2.3.1	Fixed Block Format Specification	15
6.2.3.1.1	Number of octets	15
6.2.3.1.2	Format Type Code	15
6.2.3.1.3	Flag Octet	15
6.2.3.1.4	Number of sectors per track	16
6.2.3.1.5	Number of physical octets per sector	16
6.2.3.1.6	Number of octets to be skipped during header verify	16
6.2.3.1.7	Number of fields per sector	16
6.2.3.1.8	Number of octets per field	16
6.2.3.1.9	Master Turnaround Delay	16
6.2.4	Variable Block Mode	17
6.2.4.1	Variable Block Format Specification	17
6.2.4.1.1	Number of octets	17
6.2.4.1.2	Format Type code	17
6.2.4.1.3	Flag Octet	17
6.2.4.1.4	Cell length	17
6.2.4.1.5	RPS Divisions per track	17
6.2.4.1.6	Index Mark Gap length	18
6.2.4.1.7	Home Field Data Segment length	18
6.2.4.1.8	Home Field Gap length	18
6.2.4.1.9	Home Field Skip Length	18
6.2.4.1.10	Home Field retries	18
6.2.4.1.11	Header Field Data Segment length	18
6.2.4.1.12	Header Field Gap length	18
6.2.4.1.13	Data Field Gap length	18
6.2.4.1.14	Defect Skip Segment length	18
6.3	Slave conditions	19
6.4	Dual Port (optional)	20
6.4.1	Port Enable/Disable	20
6.4.2	Slave Accessibility mode	20
6.4.2.1	Switching	21
6.4.2.2	Switch mechanism	21
6.4.3	Notification of alternate port exception condition	21
6.4.4	Attention	21
6.5	Reset	22
6.5.1	External Reset	22
6.5.2	Internal Reset	22
6.6	Head Control	22
6.7	Rotational Position Sensing (RPS) (optional)	22
6.7.1	RPS Target Sector Address	22
6.7.2	RPS Interrupt	22
6.8	Slave ECC (optional)	22
6.9	Power Sequencing (optional)	23
7	Bus Controls	24
7.1	Command/Response Controls	24
7.1.1	Load Slave Function (01)	25
7.1.1.1	Reserved for future use (00-0F)	25
7.1.1.2	Disable Alternate Port (10) (optional)	25
7.1.1.3	Enable Alternate Port (11) (optional)	25
7.1.1.4	Disable Port (12) (optional)	25
7.1.1.5	Priority Reserve (13) (optional)	25
7.1.1.6	Reserve (14) (optional)	25
7.1.1.7	Release (15) (optional)	25
7.1.1.8	Notify alternate port of format completion (16) (optional)	25