

# INTERNATIONAL STANDARD

**ISO/IEC  
9318-3**

First edition  
1990-12-15

---

## Information technology — Intelligent Peripheral Interface

### Part 3:

Device generic command set for magnetic and optical disk drives

*Technologies de l'information — Interface pour les périphériques intelligents —  
Partie 3: Jeu de commandes génériques appareil pour les disques magnétiques et optiques*



Reference number  
ISO/IEC 9318-3 : 1990 (E)

## ISO/IEC 9318-3 : 1990 (E)

## Contents

	Page
Foreword .....	xxvii
Introduction .....	xxviii
1 Scope .....	1
2 Normative reference .....	2
3 Definitions and conventions .....	3
3.1 Definitions .....	3
3.2 Conventions .....	5
4 Logical interface characteristics .....	6
4.1 Operations .....	6
4.1.1 Commands .....	6
4.1.1.1 Command types .....	6
4.1.1.2 Command stacking .....	6
4.1.1.2.1 Individual .....	6
4.1.1.2.2 Queued .....	7
4.1.1.3 Command execution order .....	7
4.1.2 Operation responses .....	8
4.1.2.1 Interrupts .....	8
4.1.2.2 Response types .....	9
4.1.2.2.1 Command completion response .....	9
4.1.2.2.2 Transfer Notification Response (optional) .....	9
4.1.2.2.3 Asynchronous response .....	9
4.1.2.2.4 Imbedded data response (optional) .....	9
4.1.2.3 Response handling .....	9
4.1.3 Physical interface error recovery considerations .....	10
4.1.3.1 Recovery from unsuccessful Slave Status octet .....	10
4.1.3.2 Recovery from bad parity on the Slave Status octet .....	10
4.2 Operation sequences .....	11
4.2.1 Slave procedures .....	11
4.2.2 Basic steps .....	11
4.2.2.1 Transmit Command packet to slave .....	11
4.2.2.2 Poll interrupts .....	12
4.2.2.3 Receive Response packet from slave .....	12
4.2.2.4 Transfer of data between master and slave .....	12
4.2.3 Operation sequence examples .....	13
4.2.3.1 Example of facility selection and individual commands .....	13
4.2.3.2 Example of facility selection and queued commands .....	13
4.2.3.3 Example of slave selection .....	14
4.2.3.4 Example of slave selection and slave control of Bus .....	14
4.3 Multiplexed data transfers (optional) .....	15
4.3.1 Physical interface Pause and Continue (optional) .....	15
4.3.2 Slave pause and master Continue .....	15
4.3.2.1 Implicit continue .....	16
4.3.2.2 Explicit continue .....	16
4.3.3 Slave control of Pause and Continue .....	16
4.3.4 Master control of Pause and Continue .....	16
4.3.5 Uses of multiplexing .....	17
4.3.5.1 One paused transfer per facility .....	17

© ISO/IEC 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland  
Printed in Switzerland

4.3.5.2 One paused transfer per slave . . . . .	17
4.3.5.3 Multiple paused transfers per slave . . . . .	17
4.3.6 Anticipated pause . . . . .	17
4.3.6.1 Master stays selected . . . . .	17
4.3.6.2 Master deselects . . . . .	18
4.3.7 Unanticipated pauses by the slave . . . . .	18
4.3.8 Unanticipated pauses by the master . . . . .	18
4.3.9 Multiplexed transfer mode identification . . . . .	18
4.4 Data groupings . . . . .	18
4.4.1 PhysicalBlocks . . . . .	19
4.4.2 DataBlocks . . . . .	19
4.4.3 Extents . . . . .	19
4.4.4 Partitions . . . . .	19
4.4.4.1 Slave-defined partitions . . . . .	20
4.4.4.1.1 Data partition . . . . .	20
4.4.4.1.2 Maintenance partitions . . . . .	20
4.4.4.2 Master-defined partitions . . . . .	20
4.4.4.2.1 Data partitions . . . . .	20
4.4.4.2.2 Maintenance partitions . . . . .	20
4.4.5 Alternate data areas . . . . .	20
4.4.6 Physical groups . . . . .	20
4.5 Media addressing definitions . . . . .	21
4.5.1 Absolute addressing . . . . .	21
4.5.2 Physical addressing . . . . .	21
4.5.3 Logical addressing . . . . .	22
4.5.4 Media defect management considerations . . . . .	22
4.6 Interface addressing definitions . . . . .	23
4.6.1 Actual Addresses . . . . .	23
4.6.2 Selection Addresses . . . . .	23
4.6.3 Command Addresses . . . . .	23
4.6.4 Facility Address . . . . .	24
4.6.5 Synonym Addresses (optional) . . . . .	24
4.6.6 Alias Addresses (optional) . . . . .	24
4.6.7 Partition parameters . . . . .	25
4.6.8 Communication addresses (optional) . . . . .	25
4.6.9 Address examples . . . . .	26
4.7 Slave and facility conditions . . . . .	26
4.7.1 Interface conditions . . . . .	27
4.7.1.1 P-Available . . . . .	27
4.7.1.2 Not P-Available . . . . .	27
4.7.1.3 Operational . . . . .	27
4.7.1.4 Not Operational . . . . .	28
4.7.1.5 P-Busy . . . . .	28
4.7.1.6 Not P-Busy . . . . .	28
4.7.1.7 L-Available . . . . .	28
4.7.1.8 Not L-Available . . . . .	28
4.7.1.9 L-Busy . . . . .	28
4.7.1.10 Not L-Busy . . . . .	28
4.7.2 General conditions . . . . .	28
4.7.2.1 Active . . . . .	28
4.7.2.2 Inactive . . . . .	28
4.7.2.3 Status Pending . . . . .	29
4.7.2.4 Reset . . . . .	29
4.7.3 Operating status . . . . .	29
4.8 Multiple ports (optional) . . . . .	30
4.8.1 Slave switching . . . . .	30
4.8.1.1 Physical switch . . . . .	31
4.8.1.2 Logical switch . . . . .	31
4.8.1.3 Mixed switch types . . . . .	32
4.8.2 Facility switching . . . . .	32