

INTERNATIONAL  
STANDARD

ISO  
6624-3

Second edition  
2017-04

---

---

---

**Internal combustion engines —  
Piston rings —**

**Part 3:  
Keystone rings made of steel**

*Moteurs à combustion interne — Segments de piston —  
Partie 3: Segments trapézoïdaux en acier*



Reference number  
ISO 6624-3:2017(E)

© ISO 2017



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

	Page
<b>Foreword</b>	<b>iv</b>
<b>Introduction</b>	<b>v</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative reference</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Overview</b>	<b>1</b>
<b>5 Ring types and designation examples</b>	<b>1</b>
5.1 Type T — Straight faced keystone ring 6°	1
5.1.1 General features	1
5.1.2 Designation	2
5.2 Type TB — Symmetrical barrel faced keystone ring 6°	2
5.2.1 General features	2
5.2.2 Designation	4
5.3 Type TBA — Asymmetrical barrel faced keystone ring 6°	4
5.3.1 General features	4
5.3.2 Designation	5
5.4 Type TM — Taper faced keystone ring 6°	5
5.4.1 General features	5
5.4.2 Designation	7
5.5 Type K — Straight faced keystone ring 15°	7
5.5.1 General features	7
5.5.2 Designation	7
5.6 Type KB — Symmetrical barrel faced keystone ring 15°	8
5.6.1 General features	8
5.6.2 Designation	8
5.7 Type KBA — Asymmetrical barrel faced keystone ring 15°	9
5.7.1 General features	9
5.7.2 Designation	9
5.8 Type KM — Taper faced keystone ring 15°	10
5.8.1 General features	10
5.8.2 Designation	10
<b>6 Common features</b>	<b>10</b>
6.1 Type T, TB, TBA, TM, K, KB, KBA, KM rings — Outside and inside rounded edges	10
6.2 Type T, TB, TBA, TM, K, KB, KBA, KM rings (positive twist type) — Internal bevel top side	11
6.3 Type TM or KM rings with partly cylindrical machined (LM) or lapped (LP) peripheral surface	12
6.4 Type T, TB, TBA, TM, K, KB, KBA, KM rings — Plating or coating configuration	12
6.4.1 Chromium plated or spray coated rings	12
6.4.2 Nitrided surface	14
6.4.3 PVD rings	15
<b>7 Force factors</b>	<b>15</b>
<b>Bibliography</b>	<b>23</b>