

INTERNATIONAL
STANDARD

ISO
7240-2

Second edition
2017-11

**Fire detection and alarm systems —
Part 2:
Fire detection control and indicating
equipment**

*Systèmes de détection et d'alarme d'incendie —
Partie 2: Équipement de contrôle et de signalisation*



Reference number
ISO 7240-2:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
4 Requirements	2
4.1 General	2
4.2 Compliance	3
4.3 Quiescent condition	3
4.4 Fire alarm condition	3
4.4.1 Reception and processing of fire signals	3
4.4.2 Indication of fire alarm condition	4
4.4.3 Indication of fire detection zones in alarm	4
4.4.4 Audible indication	4
4.4.5 Other indications during the fire alarm condition	5
4.4.6 Reset from fire alarm condition	5
4.4.7 Output of fire alarm condition	5
4.4.8 Output to fire alarm signalling function — Optional function	5
4.4.9 Control of fire alarm routing function — Optional function	6
4.4.10 Output to fire protection control function — Optional function	6
4.4.11 Delays to outputs — Optional function	7
4.4.12 Dependency on more than one alarm signal — Optional function	8
4.4.13 Alarm counter — Optional function	9
4.4.14 Output of standard emergency evacuation signal — Optional function	9
4.5 Fault warning condition	9
4.5.1 Reception and processing of fault signals	9
4.5.2 Indication of faults	9
4.5.3 Fault monitoring of fire protection control function — Optional function	11
4.5.4 Fault signals from points — Optional function	11
4.5.5 Total loss of the power supply — Optional function	11
4.5.6 System fault	11
4.5.7 Audible indication	11
4.5.8 Reset of fault indications	12
4.5.9 Fault output	12
4.5.10 Output to fault warning routing function — Optional function	12
4.6 Disabled condition — Optional function	12
4.6.1 General	12
4.6.2 Disablements	13
4.6.3 Disablement and enablement of addressable points — Optional function	13
4.6.4 Indication of the disabled condition	13
4.7 Test condition — Optional function	14
4.7.1 General requirements	14
4.7.2 Indication of test condition	14
4.7.3 Indication of fire detection zones in test state	14
4.8 Supervisory signal condition — Optional function	14
4.8.1 Reception and processing of supervisory signals	14
4.8.2 Indication of the supervisory signal condition	15
4.8.3 Indication of the supervisory signals from fire detection zones	15
4.8.4 Audible indication	15
4.8.5 Reset of supervisory signal	16
4.8.6 Supervisory signal condition output	16
4.9 Standardized input/output interface — Optional function	16
4.10 Accessibility of indications and controls	17