

INTERNATIONAL STANDARD

ISO 7457

Second edition
1997-12-15

Earth-moving machinery — Determination of turning dimensions of wheeled machines

*Engins de terrassement — Détermination des dimensions de braquage des
engins sur roues*

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licensor's members.



Reference number
ISO 7457:1997(E)

ISO 7457:1997(E)**Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7457 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 1, *Test methods relating to machine performance*.

This second edition cancels and replaces the first edition (ISO 7457:1983), which has been technically revised.

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Earth-moving machinery — Determination of turning dimensions of wheeled machines

1 Scope

This International Standard specifies methods for determining the turning radius, turning diameter, machine clearance diameter, and inside and outside tyre clearance diameters, described in the horizontal plan by a wheeled earth-moving machine with its equipment and attachments when executing a turn.

This International Standard is applicable to all types of steerable wheeled earth-moving machinery. It is applicable irrespective of the type of steering used.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 5010:1992, *Earth-moving machinery — Rubber-tyred machines — Steering requirements.*

ISO 6165:1997, *Earth-moving machinery — Basic types — Vocabulary.*

ISO 9248:1992, *Earth-moving machinery — Units for dimensions, performance and capacities, and their measurement accuracies.*

3 Definitions

For the purposes of this International Standard, the definitions given in ISO 6165 and the following apply.

3.1 turning centre: Point about which all turns of constant radius are made. (See figure 1.)

3.2 turning diameter: Diameter of the circular path described by the centre of tyre contact with the surface of the test site of the wheel describing the largest circle when the machine is executing its sharpest practicable turn under the test conditions described in clause 7, or by calculation for skid steer loaders. (See figure 1.)

3.3 turning radius: Half the turning diameter (as defined in 3.2). (See figure 1.)

3.4 machine clearance diameter: Diameter of the smallest circle which will enclose the outermost points of projection of the machine and its equipment and attachments when it executes its sharpest practical turn, under the conditions described in clause 7, or by calculation for skid steer loaders. (See figure 1.)