

INTERNATIONAL
STANDARD

ISO
7626-5

Second edition
2019-12

**Mechanical vibration and shock —
Experimental determination of
mechanical mobility —**

**Part 5:
Measurements using impact excitation
with an exciter which is not attached
to the structure**

*Vibrations et chocs mécaniques — Détermination expérimentale de la
mobilité mécanique —*

*Partie 5: Mesurages à partir d'une excitation par choc appliquée par
un excitateur non solidaire de la structure*



Reference number
ISO 7626-5:2019(E)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General characteristics of impact measurements	2
4.1 General description	2
4.2 Advantages and limitations of impact excitation	3
4.2.1 General	3
4.2.2 Nonlinearity restrictions	4
4.2.3 Signal-to-noise problems	4
4.2.4 Limited frequency resolution	4
4.2.5 Damping restrictions	4
4.2.6 Dependence on operator skill	5
5 Support of the structure under test	5
5.1 General	5
5.2 Ungrounded measurements	5
5.3 Grounded measurements	5
6 Application of the excitation	5
6.1 Impactor design	5
6.2 Force spectrum characteristics	6
6.3 Control of the frequency range of excitation	10
6.4 Avoidance of impactor double hits	10
7 Transducer system	12
7.1 General	12
7.2 Impactor calibration	12
8 Processing of the transducer signals	13
8.1 Filtering	13
8.2 Transient capture characteristics	13
8.3 Sampling relationships	14
8.4 Avoidance of saturation (clipping)	15
8.5 Windowing techniques	15
8.5.1 Force signal	15
8.5.2 Windowing the response signals	19
8.6 Averaging techniques	23
9 Tests for validity of the measurements	24
9.1 Coherence function	24
9.2 Repeatability check	25
9.3 Reciprocity check	25
9.4 Linearity check	25
9.5 Comparison with measurements using an attached exciter	25
Annex A (informative) Correction of mobility measurements for the effects of exponential windowing	26
Bibliography	28