
**Hydraulic fluid power — Mounting
dimensions for accessories for single
rod cylinders, 16 MPa (160 bar)
medium and 25 MPa (250 bar) series**

*Transmissions hydrauliques — Dimensions d'interchangeabilité des
accessoires pour vérins à simple tige, 16 MPa (160 bar) série moyenne
et 25 MPa (250 bar)*





COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Mounting dimensions	2
5 Tolerances	2
6 Application instructions	2
6.1 Installation.....	2
6.1.1 Shaft for pivot pin, plain	2
6.1.2 Shaft for pivot pin, spherical bearing.....	2
6.1.3 Tilting angle.....	2
6.1.4 Rod clevis.....	2
6.2 Lubrication.....	3
7 Designation	3
8 Identification statement (reference to this document)	3
Bibliography	14