

# INTERNATIONAL STANDARD

ISO  
8630-2

First edition  
1987-06-15



---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION  
ORGANISATION INTERNATIONALE DE NORMALISATION  
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

---

**Information processing — Data interchange on  
130 mm (5.25 in) flexible disk cartridges using modified  
frequency modulation recording at 13 262 ftprad, on  
80 tracks on each side —**

**Part 2:**  
Track format A for 77 tracks

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 8630-2 was prepared by Technical Committee ISO/TC 97, *Information processing systems*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

<b>Contents</b>		<b>Page</b>
<b>0</b>	Introduction .....	1
<b>1</b>	Scope and field of application .....	1
<b>2</b>	Conformance .....	1
<b>3</b>	References .....	1
<b>4</b>	General requirements .....	1
<b>4.1</b>	Mode of recording .....	1
<b>4.2</b>	Track location tolerance of the recorded flexible disk cartridge .....	2
<b>4.3</b>	Recording offset angle .....	2
<b>4.4</b>	Density of recording .....	2
<b>4.5</b>	Flux transition spacing .....	2
<b>4.6</b>	Average Signal Amplitude .....	3
<b>4.7</b>	Byte .....	3
<b>4.8</b>	Sector .....	3
<b>4.9</b>	Cylinder .....	3
<b>4.10</b>	Cylinder Number .....	3
<b>4.11</b>	Data capacity of a track .....	3
<b>4.12</b>	Hexadecimal notation .....	3
<b>4.13</b>	Error Detection Characters (EDC) .....	3
<b>5</b>	Track layout after the first formatting for track 00, side 0 .....	3
<b>5.1</b>	Index Gap .....	4
<b>5.2</b>	Sector Identifier .....	4
<b>5.3</b>	Identifier Gap .....	4
<b>5.4</b>	Data Block .....	4
<b>5.5</b>	Data Block Gap .....	4
<b>5.6</b>	Track Gap .....	4