
**Cranes — Design principles for loads
and load combinations —**

Part 5:
**Overhead travelling and portal
bridge cranes**

*Appareils de levage à charge suspendue — Principes de calcul des
charges et des combinaisons de charges —*

Partie 5: Ponts roulants et ponts portiques





COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	1
5 Loads and applicable factors	3
5.1 Regular loads.....	3
5.1.1 General.....	3
5.1.2 Hoisting and gravity effects acting on the mass of the crane.....	3
5.1.3 Hoisting an unrestrained grounded load.....	3
5.1.4 Loads caused by travelling on an uneven surfaces.....	5
5.1.5 Loads caused by acceleration of drives.....	5
5.1.6 Positioning of loads.....	6
5.1.7 Loads induced by displacements.....	7
5.2 Occasional loads.....	8
5.2.1 General.....	8
5.2.2 Loads caused by skewing.....	8
5.3 Exceptional loads.....	12
5.3.1 General.....	12
5.3.2 Test loads.....	13
5.3.3 Loads due to buffer forces.....	13
5.3.4 Loads caused by emergency cut-out.....	13
5.3.5 Loads caused by apprehended failure of mechanism or components.....	13
5.3.6 Loads due to dynamic cut-off of hoisting movement by lifting force limiters.....	14
5.4 Miscellaneous loads.....	16
6 Applicable loads, load combinations and factors	16
7 Combination of acceleration effects	19
Annex A (informative) Skewing loads: Assumptions for simplified calculating methods	21
Bibliography	28