

INTERNATIONAL  
STANDARD

ISO/IEC  
**11557**

First edition  
1992-12-15

---

---

**Information technology — 3,81 mm wide  
magnetic tape cartridge for information  
interchange — Helical scan recording —  
DDS-DC format using 60 m and 90 m  
length tapes**

*Technologies de l'information — Cartouche de bande magnétique de  
3,81 mm de large pour l'échange d'information — Enregistrement  
hélicoïdal — Format DDS-DC utilisant des bandes de 60 m et 90 m de  
long*



Reference number  
ISO/IEC 11557:1992(E)

<b>Contents</b>	<b>Page</b>
<b>Section 1 - General</b>	<b>1</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Conformance</b>	<b>2</b>
<b>3.1 Magnetic tape cartridge</b>	<b>2</b>
<b>3.2 Generating system</b>	<b>2</b>
<b>3.3 Receiving system</b>	<b>2</b>
<b>4 Definitions</b>	<b>3</b>
<b>4.1 Absolute Frame Number</b>	<b>3</b>
<b>4.2 Access Point</b>	<b>3</b>
<b>4.3 algorithm</b>	<b>3</b>
<b>4.4 Automatic Track Finding</b>	<b>3</b>
<b>4.5 Area ID</b>	<b>3</b>
<b>4.6 Average Signal Amplitude</b>	<b>3</b>
<b>4.7 azimuth</b>	<b>3</b>
<b>4.8 back surface</b>	<b>3</b>
<b>4.9 byte</b>	<b>3</b>
<b>4.10 cartridge</b>	<b>3</b>
<b>4.11 Channel Bit</b>	<b>3</b>
<b>4.12 Codeword</b>	<b>3</b>
<b>4.13 Data Format ID</b>	<b>3</b>
<b>4.14 Early Warning Point</b>	<b>3</b>
<b>4.15 End of Data</b>	<b>3</b>
<b>4.16 Entity</b>	<b>3</b>
<b>4.17 Error Correcting Code</b>	<b>4</b>
<b>4.18 flux transition position</b>	<b>4</b>
<b>4.19 flux transition spacing</b>	<b>4</b>
<b>4.20 frame</b>	<b>4</b>
<b>4.21 Housekeeping Frame</b>	<b>4</b>
<b>4.22 Logical Beginning of Tape</b>	<b>4</b>
<b>4.23 magnetic tape</b>	<b>4</b>
<b>4.24 Master Standard Amplitude Calibration Tape</b>	<b>4</b>
<b>4.25 Master Standard Reference Tape</b>	<b>4</b>

<b>4.26</b>	Optimum Recording Field	4
<b>4.27</b>	Partition boundary	4
<b>4.28</b>	Physical Beginning of Tape	4
<b>4.29</b>	Physical End of Tape	4
<b>4.30</b>	physical recording density	4
<b>4.31</b>	pre-recording condition	4
<b>4.32</b>	processing	4
<b>4.33</b>	processed data	4
<b>4.34</b>	Processed Record	5
<b>4.35</b>	Processed Record Sequence	5
<b>4.36</b>	Record	5
<b>4.37</b>	Reference Recording Field	5
<b>4.38</b>	reprocessing	5
<b>4.39</b>	Secondary Standard Amplitude Calibration Tape	5
<b>4.40</b>	Secondary Standard Reference Tape	5
<b>4.41</b>	Separator Mark	5
<b>4.42</b>	Standard Reference Amplitude	5
<b>4.43</b>	Tape Reference Edge	5
<b>4.44</b>	Test Recording Current	5
<b>4.45</b>	track	5
<b>4.46</b>	Unprocessed Data	5
<b>4.47</b>	Unprocessed Record	5
<b>4.48</b>	Virtual End of Tape	5
<b>5</b>	Environment and safety	5
<b>5.1</b>	Testing environment	5
<b>5.2</b>	Operating environment	6
<b>5.3</b>	Storage environment	6
<b>5.4</b>	Transportation	6
<b>5.5</b>	Safety	6
<b>5.6</b>	Flammability	6
<b>Section 2 - Requirements for the case</b>		6
<b>6</b>	Dimensional and mechanical characteristics of the case	6
<b>6.1</b>	General	6
<b>6.2</b>	Overall dimensions (figures 6 and 7)	7
<b>6.3</b>	Loading grip (figure 6)	8
<b>6.4</b>	Holding areas (figure 6)	8
<b>6.5</b>	Notches of the lid (figures 5 and 8)	8
<b>6.6</b>	Lid dimensions (figures 6 to 8)	8
<b>6.7</b>	Optical detection of the beginning and end of tape (figures 9 and 12)	9
<b>6.8</b>	Bottom side (figures 10 and 11)	10
<b>6.8.1</b>	Locking mechanism of the slider	10
<b>6.8.2</b>	Access holes	10
<b>6.8.3</b>	Recognition, sub-datums, and write-inhibit holes	11
<b>6.8.4</b>	Datum holes	12
<b>6.8.5</b>	Access room for tape guides	13
<b>6.8.6</b>	Holes for accessing the hubs	13
<b>6.8.7</b>	Internal structure of the lower half (figure 12)	13