

TECHNICAL SPECIFICATION

ISO/TS
13725

Third edition
2021-09

Hydraulic fluid power — Method for evaluating the buckling load of a hydraulic cylinder

*Transmissions hydrauliques — Méthode d'évaluation de la charge de
flambage d'un vérin hydraulique*



Reference number
ISO/TS 13725:2021(E)

© ISO 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and units	2
4.1 General	2
4.2 Additional notations	3
5 General principles	3
5.1 Purpose	3
5.2 Description	3
5.3 Dimensional layout of hydraulic cylinder	4
5.4 Common calculation of maximum stress in the rod (for all mounting types) σ_{\max}	5
5.4.1 General	5
5.4.2 Deflexion curve	6
5.4.3 Bending moment	6
5.4.4 Maximum value of the bending moment	6
5.4.5 Maximum stress of the piston rod	7
5.4.6 Mounting types of the cylinder tube and piston rod	7
6 Case of pin-mounted hydraulic cylinders	8
6.1 Model of the hydraulic cylinder and unknown values	8
6.2 Linear system	8
6.3 Critical buckling load	9
6.4 Greatest allowable compressive load	9
7 Case of hydraulic cylinders fixed at the beginning of the cylinder tube and pin mounted at the end of the piston rod	10
7.1 Critical buckling load	10
7.2 Linear system	10
8 Case of hydraulic cylinders pin mounted at the beginning of the cylinder tube and fixed at the end of the piston rod	11
8.1 Critical buckling load	11
8.2 Linear system	11
9 Case of hydraulic cylinders fixed at both ends	12
9.1 Critical buckling load	12
9.2 Linear system	13
10 Case of hydraulic cylinders fixed at the beginning of the cylinder tube and free at the end of the piston rod	14
10.1 Critical buckling load	14
10.2 Linear system	15
11 Case of hydraulic cylinders fixed at both ends with free movement allowed at the end of the piston rod	16
11.1 Critical buckling load	16
11.2 Linear system	17
Annex A (informative) Example of numerical results	18
Bibliography	20