

---

---

**Information technology — 3,81 mm wide  
magnetic tape cartridge for information  
interchange — Helical scan recording —  
DDS-3 format using 125 m length tapes**

*Technologies de l'information — Cartouche de bande magnétique de  
3,81 mm de large pour l'échange d'information — Enregistrement par  
balayage en spirale — Format DDS-3 utilisant des bandes de 125 m de  
long*

**Contents**

<b>1 Scope</b>	1
<b>2 Conformance</b>	1
2.1 Magnetic tape cartridge	1
2.2 Generating drive	1
2.3 Receiving drive	1
<b>3 Normative References</b>	2
<b>4 Definitions</b>	2
4.1 Absolute Frame Number (AFN)	2
4.2 a.c. erase	2
4.3 Access Point	2
4.4 algorithm	2
4.5 Area ID	2
4.6 Average Signal Amplitude	2
4.7 azimuth	2
4.8 back surface	2
4.9 byte	2
4.10 cartridge	2
4.11 Channel bit	2
4.12 Codeword	2
4.13 Data Format ID	3
4.14 Early Warning Point (EWP)	3
4.15 End of Data (EOD)	3
4.16 Entity	3
4.17 Error Correcting Code (ECC)	3
4.18 flux transition position	3
4.19 flux transition spacing	3
4.20 Fragment	3
4.21 Frame	3
4.22 Housekeeping Frame	3
4.23 Logical Beginning of Tape (LBOT)	3
4.24 magnetic tape	3
4.25 Master Standard Amplitude Calibration Tape	3
4.26 Master Standard Reference Tape	3
4.27 Optimum Recording Field	3
4.28 Partition Boundary	3
4.29 Physical Beginning of Tape (PBOT)	3
4.30 Physical End of Tape (PEOT)	3
4.31 physical recording density	3
4.32 pre-recording condition	3
4.33 processing	3
4.34 processed data	3
4.35 Processed Record	3
4.36 Processed Record Sequence	3

© ISO/IEC 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland  
 Printed in Switzerland

4.37 record	3
4.38 Reference Recording Field	3
4.39 reprocessing	4
4.40 Secondary Standard Amplitude Calibration Tape	4
4.41 Secondary Standard Reference Tape	4
4.42 Separator Mark	4
4.43 Standard Reference Amplitude	4
4.44 Tape Reference Edge	4
4.45 Test Recording Current	4
4.46 track	4
4.47 unprocessed data	4
4.48 Unprocessed Record	4
4.49 Virtual End of Tape (VEOT)	4
<b>5 Conventions and Notations</b>	<b>4</b>
<b>6 Acronyms</b>	<b>4</b>
<b>7 Environment and safety</b>	<b>5</b>
7.1 Testing environment	5
7.2 Operating environment	5
7.3 Storage environment	5
7.4 Transportation	5
7.5 Safety	5
7.6 Flammability	5
<b>8 Dimensional and mechanical characteristics of the case</b>	<b>6</b>
8.1 General	6
8.2 Overall dimensions	6
8.3 Loading grip	7
8.4 Holding areas	7
8.5 Notches of the lid	7
8.6 Lid dimensions	7
8.7 Optical detection of the beginning and end of tape	8
8.8 Bottom side	8
8.8.1 Locking mechanism of the slider	9
8.8.2 Access holes	9
8.8.3 Recognition, sub-datums, and write-inhibit holes	9
8.8.4 Datum holes	11
8.8.5 Access room for tape guides	11
8.8.6 Holes for accessing the hubs	11
8.8.7 Internal structure of the lower half	12
8.8.8 Light path	13
8.8.9 Support Areas	13
8.8.10 Datum Areas	13
8.8.11 Relationship between Support and Datum Areas and Reference Plane Z	13
8.9 Hubs	13
8.10 Attachment of leader and trailer tapes	14
8.11 Interface between the hubs and the drive spindles	14
8.12 Opening of the lid	14
8.13 Release of the hub locking mechanism	14
8.14 Label areas	15
8.15 Requirement for autoloaders	15
<b>9 Mechanical, physical and dimensional characteristics of the tape</b>	<b>27</b>