
**Diesel engines — NO_x reduction agent
AUS 32 —**

Part 5:
Refilling interface for passenger cars

Moteurs diesel — Agent AUS 32 de réduction des NO_x —

Partie 5: Interface de remplissage pour voitures particulières





COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	2
4.1 Functional requirements.....	2
4.2 Filler neck.....	4
4.3 Filler nozzle.....	6
4.4 Clearance space.....	7
4.4.1 General.....	7
4.4.2 Minimum clearance "Class A".....	7
4.4.3 Minimum clearance "Class B".....	8
5 Testing	10
5.1 General test requirements.....	10
5.2 Determination of spillage from nozzle.....	10
5.3 Determination of smell.....	10
5.3.1 General.....	10
5.3.2 Preconditioning the system to establish constant test conditions.....	11
5.3.3 Test procedure.....	11
5.4 Minimum strength of filler neck.....	12
5.4.1 General.....	12
5.4.2 Testing simulating misuse.....	12
5.4.3 Testing in axial direction.....	13
Annex A (informative) Filler neck with ribs	15
Bibliography	16