

INTERNATIONAL  
STANDARD

ISO  
23449

First edition  
2020-10

---

---

---

**Corrosion of metals and alloys —  
Multielectrode arrays for corrosion  
measurement**

*Corrosion des métaux et alliages — Assemblages multi-électrodes  
pour la mesure de la corrosion*



Reference number  
ISO 23449:2020(E)

© ISO 2020



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b>	<b>iv</b>
<b>Introduction</b>	<b>v</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Principle</b>	<b>3</b>
4.1 Multielectrode arrays	3
4.2 Coupled multielectrode array (CMA)	3
4.3 Multielectrode array with closely packed electrodes for studying spatiotemporal behaviour of localized corrosion	4
4.4 Coupled multielectrode array sensor (CMAS)	5
4.4.1 CMAS for corrosion monitoring	5
4.4.2 CMAS used without polarization to measure corrosion rate at free corrosion potential	6
4.4.3 CMAS used to evaluate the effectiveness of cathodic protection and the effect of stray current	6
4.5 Multielectrode arrays for high throughput measurements	7
4.6 Multielectrode arrays for other applications	7
<b>5 Instrumentation</b>	<b>8</b>
5.1 Potential measurement	8
5.2 Coupling current measurement	8
5.3 Effective coupling of individual electrodes	9
5.3.1 Coupling with multichannel ZVA	9
5.3.2 Coupling with wires and measuring current with a single ZVA	10
<b>6 Fabrication of multielectrode array</b>	<b>10</b>
6.1 Electrode preparation	10
6.2 Number of electrodes	10
6.3 Mounting of electrodes	11
6.4 Surface coating on electrodes for preventing crevice corrosion	11
6.5 Electrode configuration	11
6.6 Size of electrodes	11
6.7 Spacing of electrodes for spatiotemporal studies	12
6.8 Spacing of electrodes for corrosion monitoring in oil and gas application	12
6.9 Size and spacing of the electrodes for high throughput studies	12
<b>7 Test procedure</b>	<b>12</b>
<b>8 Test report</b>	<b>13</b>
<b>Annex A (informative) Typical results from multielectrode array with closely packed electrodes for studying spatiotemporal behaviour of localized corrosion</b>	<b>14</b>
<b>Annex B (informative) Typical results from a CMAS for corrosion monitoring</b>	<b>15</b>
<b>Annex C (informative) Example reports</b>	<b>17</b>
<b>Bibliography</b>	<b>18</b>