

INTERNATIONAL
STANDARD

ISO
24046

First edition
2022-08

**Fine ceramics (advanced ceramics,
advanced technical ceramics) —
Methods of tests for reinforcements
— Determination of the tensile
properties of resin-impregnated yarns**

*Céramiques techniques (céramique technique, céramique technique
avancée) — Méthodes d'essais pour renforts — Détermination des
propriétés en traction des fils imprégnés de résine*



Reference number
ISO 24046:2022(E)

© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	3
5 Apparatus and material	3
5.1 Resin	3
5.2 Impregnation apparatus	3
5.3 Curing oven with temperature control	4
5.4 Tensile-testing machine and extensometer	4
5.4.1 Tensile-testing machine	4
5.4.2 Extensometer	4
5.5 Balance	4
5.6 Ruler	4
6 Test specimens	4
6.1 Number of test specimens	4
6.2 Impregnation of test specimens	4
6.3 Determination of other fibre properties	5
6.3.1 General	5
6.3.2 Linear density of the yarn	5
6.3.3 Size content of the yarn	5
6.3.4 Density of the ceramic fibre	5
6.4 Criteria for selection of the test specimens	5
6.4.1 Specimens	5
6.4.2 Resin content of the specimens	5
6.4.3 Impregnated yarn	6
7 Atmospheres for conditioning and testing	6
8 Procedure for tensile testing	6
8.1 Procedure	6
8.2 Determination of load train compliance	6
8.3 Test validity	6
9 Calculation of results	7
9.1 Tensile strength	7
9.2 Calculation of the load train compliance	7
9.3 Calculation of instantaneous total compliance and longitudinal deformation of resin-impregnated yarn	8
9.4 Tensile modulus of elasticity	9
9.5 Tensile strain at maximum force (percentage elongation at failure)	10
9.5.1 Calculation method (1)	10
9.5.2 Calculation method (2)	11
10 Statistics	11
11 Test report	11
Annex A (informative) Examples of heat-curable epoxy-resin systems	13
Annex B (informative) Examples of resin-impregnating apparatus	14
Annex C (informative) Example of extensometer	15
Bibliography	17