

FLIGHT MANAGEMENT COMPUTER SYSTEM

ARINC CHARACTERISTIC 702-6

PUBLISHED: JUNE 10, 1994



Prepared by AIRLINES ELECTRONIC ENGINEERING COMMITTEE Published by AERONAUTICAL RADIO, INC. 2551 RIVA ROAD, ANNAPOLIS, MARYLAND 21401

Copyright© 1994 by AERONAUTICAL RADIO, INC. 2551 Riva Road Annapolis, Maryland 21401-7465 USA

ARINC CHARACTERISTIC 702-6© FLIGHT MANAGEMENT COMPUTER SYSTEM

Published: June 10, 1994

	Prepared by the Airlines Electronic Engineering Committee	
Characteristic 702	Adopted by the Airlines Electronic Engineering Committee:	December 7, 1978
Characteristic 702	Adopted by the Industry:	February 28, 1979
Characteristic 702-1	Adopted by the Airlines Electronic Engineering Committee:	August 29, 1979
Characteristic 702-2	Adopted by the Airlines Electronic Engineering Committee:	March 12, 1981
Characteristic 702-3	Adopted by the Airlines Electronic Engineering Committee:	December 9, 1981
Characteristic 702-4	Adopted by the Airlines Electronic Engineering Committee:	October 25, 1989
Characteristic 702-5	Adopted by the Airlines Electronic Engineering Committee:	January 31, 1992
Characteristic 702-6	Adopted by the Airlines Electronic Engineering Committee:	June 10, 1994

8

ARINC CHARACTERISTIC 702 TABLE OF CONTENTS

ITEM PAGE SUBJECT INTRODUCTION AND DESCRIPTION 1.0 1 Purpose 1.1 1 1.2 Summary of Operational Characteristics 1 Brief Description of the System 1.3 1 Unit Description 1.4 2 2 2 2 2 2 2 2 2 2 2 2 2 1.4.1 Flight Management Computer (FMC) Unit Control/Display Unit (CDU) 1.4.2 1.4.3 Flight Data Storage Unit (Optional) Interchangeability 1.5 1.5.1 General Interchangeability Desired for the ARINC 702 1.5.2 Flight Management Computer System 2 "Generation Interchangeability" Considerations 1.5.3 2 1.6 Integrity and Availability 2 1.7 **Regulatory Approval** 2.0 INTERCHANGEABILITY STANDARDS 3 3 3 3 3 3 3 3 4 2.1 Introduction 2.2 Form Factor, Connectors and Index Pin Coding 2.2.1 Flight Management Computer 2.2.2 Control/Display Unit (CDU) 2.2.3 Optional Flight Data Storage Unit (FDSU) 2.3 Interwiring 2.4 Power Circuitry 4 4 2.4.1 Primary Power Input Power Control Circuitry 2.4.2 2.4.3 4 The Common Ground 2.4.4The AC Common Cold 4 4 4 4 2.5 **Environmental Conditions** Thermal Interface and Design 2.5.12.5.1.1 FMC 4 2.5.1.2 CDU Weights 4 2.6 System Functions and Signal Characteristics 5 2.7 2.8Grounding and Bonding 5 SYSTEM DESIGN CONSIDERATIONS 3.0 6 3.1 System Configurations 6 3.1.1 Single System Configuration 6 Single System/Dual CDU Configuration 3.1.26 3.1.3 **Dual System Configuration** 6 3.2 **Basic System Functions** 6 3.2.1 Performance Management 6 General 3.2.1.1 6 3.2.1.2 Performance Data Base 6 3.2.1.3 **Optimum Flight Path** 6 3.2.1.4 77777778888 Performance Data Control and Display 3.2.2 Lateral Navigation and Guidance 3.2.2.1 Lateral Navigation 3.2.2.2 Lateral Guidance 3.2.3 Vertical Navigation and Guidance 3.2.3.1 Vertical Navigation 3.2.3.2 Vertical Guidance 3.2.4 Thrust Axis Control 3.2.5 4D Guidance (Growth Option) Electronic Flight Instrument System Management 3.2.6 3.2.7 Data Update Interface 3.2.8 **IRS** Initialization and Heading Set 8 **GNSS** Initialization 3.2.9 **Operational Features and Technical Considerations** 8 3.3

Performance Management Computation

3.3.1