to ASME B16.10-2022 Face-to-Face and End-to-End Dimensions of Valves

Several column headings in Tables 1.3-1 and 1.3-3 of ASME B16.10-2022 were inadvertently misaligned. The corrected pages, 13 and 21, follow this cover sheet.

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS Two Park Avenue, New York, NY 10016-5990

March 2023



Table 1.3-1 Class 125 Cast Iron Flanged and Class 150 Steel Flanged and Buttwelding End Valves, Face-to-Face and End-to-End Dimensions (Cont'd)

19	20	21	22	23	
	Cl	ass 150 Steel	<u>.</u>		1
Flanged End [1.5 mm (0.06 in.) Raised Face]	Pl	F., J	Y47-13:	- P J	
and Welding End	Flanged End		Welding End		=
	Ball I				_
Y-Globe and Y-Swing Check, A and B	Long Pattern, <i>A</i>	Short Pattern, <i>A</i>	Long Pattern, <i>B</i>	Short Pattern, <i>B</i>	Nominal Valve Size, DN (NPS)
	1372 (54.00) (13)		1524 (60.00)		800 (32)
	1473 (58.00) (13)		1626 (64.00)		850 (34)
	1524 (60.00) (13)		1727 (68.00)	•••	900 (36)
	***		***		1000 (40)
			•••		1050 (42)
			•••		1200 (48)
			***		1350 (54)
			***		1500 (60)
•••			***	•••	1650 (66)
					1800 (72)

13