

Issued 1989-09
Reaffirmed 2004-06
Stabilized 2011-07

Superseding AIR1168/6

Aircraft Fuel Weight Penalty Due to Air Conditioning

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by the AC-9 Technical Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AIR1168/6A>**

Characteristics of Equipment Components, Equipment Cooling System Design, and Temperature Control System Design

AIR1168/6

$$P_{hp} = \frac{\Delta p Q_g}{1714}$$

$$NTU = \frac{AU_{av}}{C_{min}} = \frac{1}{C_{min}} \int_0^A U dA$$

$$q = UA (LMTD)$$

$$LMTD = \frac{\Delta t_{max} - \Delta t_{min}}{\ln \frac{\Delta t_{max}}{\Delta t_{min}}}$$

$$Work = p_1 (V_1 - V_4) \ln \frac{p_1}{p_2}$$

$$W = \frac{31.92 C_d p_1 144 A}{\sqrt{T_1}}$$

$$\text{Capacity rate ratio} = \left[\frac{C_{min}}{C_{max}} \right]$$

$$Y = \left[\left(\frac{p_{11}}{p_{s3}} \right)^{(\gamma-1)/\gamma} - 1 \right]$$

$$\Delta p_r = p_{amb} (1 + 0.2 M^2)^{3.5} - p_{amb}$$

$$N_s = \frac{n \sqrt{Q_g}}{(H)^{3/4}}$$

SAE Aerospace Applied Thermodynamics Manual

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL

PREFACE

This document is one of 14 Aerospace Information Reports (AIR) of the Third Edition of the SAE Aerospace Applied Thermodynamics Manual. The manual provides a reference source for thermodynamics, aerodynamics, fluid dynamics, heat transfer, and properties of materials for the aerospace industry. Procedures and equations commonly used for aerospace applications of these technologies are included.

In the Third Edition, no attempt was made to update material from the Second Edition nor were SI units added. However, all identified errata were corrected and incorporated and original figure numbering was retained, insofar as possible.

The SAE AC-9B Subcommittee originally created the SAE Aerospace Applied Thermodynamics Manual and, for the Third Edition, used a new format consisting of AIR1168/1 through AIR1168/10. AIR1168/11 through AIR1168/14 were created by the SAE SC-9 Committee.

The AIRs comprising the Third Edition are shown below. Applicable sections of the Second Edition are shown parenthetically in the third column.

AIR1168/1	Thermodynamics of Incompressible and Compressible Fluid Flow	(1A,1B)
AIR1168/2	Heat and Mass Transfer and Air-Water Mixtures	(1C,1D,1E)
AIR1168/3	Aerothermodynamic Systems Engineering and Design	(3A,3B,3C,3D)
AIR1168/4	Ice, Rain, Fog, and Frost Protection	(3F)