

REV.  
B

AS3418™

RATIONALE

DELETE RADIUS AT TRANSITION OF WRENCH FLATS AND BASE FLANGE, UPDATE FEATURE CONTROL FRAME FOR STRAIGHTNESS, ADD EDGE DISTANCE EXCEPTION FOR HEAD MARKING, ADD SURFACE TEXTURE REQUIREMENTS FOR HEAD, WRENCH FLATS AND BOLT END, ADD NEW NOTE FOR DISPOSITION OF EXISTING INVENTORY, UPDATE FPI REFERENCE AND ADD STANDARD SENSITIVITY REQUIREMENT, FIGURE 1 RE-DRAWN, AND GENERAL EDITORIAL CHANGES.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - BOLT

For more information on this standard, visit <https://www.sae.org/standards/content/AS3418B/>



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7467 /3/



**AEROSPACE STANDARD**  
BOLT, MACHINE, DOUBLE HEX, EXT WASHER  
HEAD, CLOSE TOL. SHANK, UNS N07718, 185 KSI MIN,  
.2500-28UNJF-3A (STRESS RUPTURE RESISTANT)

**AS3418™**  
SHEET 1 OF 3

**REV. B**

ISSUED 1995-12 REVISED 2017-06 REAFFIRMED 2022-04