

Issued 1998-08
Revised 1992-03
Stabilized 2012-05
Superseding AS4075

High Speed Ring Bus (HSRB) Standard

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE AS-1A Avionic Networks Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS4075A>**

TABLE OF CONTENTS

1.	SCOPE	4
2.	APPLICABLE DOCUMENTS	4
2.1	SAE Publications	4
2.2	Glossary	4
2.2.1	Definitions	4
2.3	Acronyms	5
3.	GENERAL REQUIREMENTS	11
3.1	General Description	11
3.1.1	Ring Station	12
3.1.2	Ring Interface Module	12
3.1.3	Ring Control	12
3.1.4	Ring Access	15
3.1.5	Data Coding	15
3.1.6	Station Addressing	15
3.1.7	Message Acknowledgement	15
3.1.8	Message Priority Levels	15
3.1.9	Types of Service	16
3.1.10	Adaptability	16
3.1.11	Media Requirements	16
3.1.12	Error and Fault Detection and Recovery	16
3.1.13	Loop Back	16
3.1.14	Reconfiguration	16
3.1.15	Synchronization	18
3.1.16	Dual Ring HSRB	18
3.2	Operational Requirements	18
3.2.1	Serial Transmission	18
3.2.2	Word Length	18
3.2.3	Message Length	18
3.2.4	Electrical Isolation	18
3.2.5	Self-Test	18
3.3	Performance Requirements	19

TABLE OF CONTENTS (Continued)

3.3.1	Station Delay	19
3.4	Semantics	19
3.4.1	Entities	19
3.4.2	Symbols	19
3.4.3	Protocol Data Units	20
3.4.4	Fields	23
3.5	Protocols	39
3.5.1	Protocol State Definitions	39
3.5.2	Priority Operation	66
3.5.3	Multiple Short Message Frame Option	66
3.5.4	Ring Acquisition	67
3.5.5	Message Frame Transmission	68
3.5.6	Message Frame Stripping	68
3.5.7	Token Issuance	68
3.5.8	Types of Service	68
3.5.9	Message Frame Retry	69
3.5.10	Station Operation	69
3.5.11	Message Receipt	70
3.5.12	Error Detection and Recovery	70
3.5.13	Station Insertion	74
3.5.14	Loss or Acquisition of Input	74
3.5.15	Reconfiguration (Beacon Mode)	74
4.	QUALITY ASSURANCE	80
4.1	General	80
4.2	Verification Methods	80
4.3	Performance Verification	80
4.4	Test Plan	80
5.	PHYSICAL MEDIA IMPLEMENTATION	86
6.	PREPARATION FOR DELIVERY	86
7.	NOTES	86
FIGURE 3.1-1	Single Ring.	12
FIGURE 3.1-2	Dual Ring.	12
FIGURE 3.1.1-1	Station Interface.	13
FIGURE 3.1.1-2	Additional Redundancy.	14
FIGURE 3.1.13-1	Station With Loop Back.	17
FIGURE 3.1.13-2	Loop Back Excluding a Fault	17
FIGURE 3.4.1-1	Signaling and Code Bits	19