



AEROSPACE STANDARD

AS5652™

REV. A

Issued	2005-12
Reaffirmed	2013-04
Revised	2018-01

Superseding AS5652

10 Megabit/sec Network Configuration Digital Time Division Command/Response Multiplex Data Bus

RATIONALE

Revision A corrects Figure numbers in the captions. There were no other changes to the content.

FOREWORD

This standard was developed in conjunction with the Miniature Munitions Interface Standard in order to support a distributed RT point-to-point network configuration.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2018 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE WEB ADDRESS:

**SAE values your input. To provide feedback on this
Technical Report, please visit**
<http://standards.sae.org/AS5652A>

TABLE OF CONTENTS

1.	SCOPE.....	3
1.1	Purpose.....	3
1.2	Field of Application.....	3
2.	REFERENCES.....	3
2.1	Applicable Documents.....	3
2.1.1	SAE Publications.....	4
2.1.2	TIA Publications.....	4
2.1.3	U.S. Government Publications.....	4
2.2	Definitions.....	4
2.3	Acronymns and Abbreviations.....	6
3.	GENERAL REQUIREMENTS.....	7
3.1	Test and Operating Requirements.....	7
3.2	Data Bus Operation.....	7
3.3	Characteristics.....	8
3.3.1	Data Form.....	8
3.3.2	Bit Priority.....	8
3.3.3	Transmission Method.....	8
3.4	Terminal Operation.....	18
3.4.1	Common Operation.....	18
3.4.2	Bus Controller Operation.....	19
3.4.3	Remote Terminal.....	19
3.4.4	Monitor Operation.....	20
3.5	Hardware Characteristics.....	20
3.5.1	Data Bus Characteristics.....	20
3.5.2	Terminal Characteristics.....	21
4.	OPERATIONAL MODES AND GUIDELINES.....	25
4.1	Bus Controller and Logical Hub.....	25
4.1.1	Logical Hub.....	25
4.2	Multiplex Selection Criteria.....	27
4.3	Line Connections.....	27
4.4	Required Mode Codes.....	28
4.5	Use of Broadcast Option.....	28
5.	NOTES.....	28
5.1	Revision Indicator.....	28
Figure 1	Data bus network configuration.....	3
Figure 2	BC logical hubstar architecture.....	5
Figure 3	Data bus with subsystems and monitors.....	7
Figure 4	Data encoding.....	9
Figure 5	Word formats.....	9
Figure 6A	Command and status sync waveform.....	10
Figure 6B	Data word sync.....	14
Figure 7	Information transfer formats.....	17
Figure 8	Broadcast information transfer formats.....	17
Figure 9	Intermessage gap and RT response time.....	18
Figure 10	Example implementation of BC to RT interface line cable.....	21
Figure 11	Terminal I/O characteristics.....	22
Figure 12	Output waveform.....	22
Figure 13	Location "A" on a BC to RT interface example.....	24
Figure 14	Three operating modes of logic level hub.....	26
Table 1	Assigned mode codes.....	13
Table 2	Criteria for acceptance or rejection of a terminal for the noise rejection test total words received by the terminal (in multiples of 10 ⁷).....	24

1. SCOPE

This SAE Aerospace Standard (AS) contains requirements for a digital time division command/response multiplex data bus, for use in systems integration that is functionally similar to MIL-STD-1553B with Notice 2 but with a star topology and some deleted functionality. Even with the use of this document, differences may exist between multiplex data buses in different system applications due to particular application requirements and the options allowed in this document. The system designer must recognize this fact and design the multiplex bus controller (BC) hardware and software to accommodate such differences. These designer selected options must exist to allow the necessary flexibility in the design of specific multiplex systems in order to provide for the control mechanism, architectural redundancy, degradation concept, and traffic patterns peculiar to the specific application requirements.

1.1 Purpose

This document establishes requirements for digital, command/response, time division multiplexing (Data bus) techniques. It encompasses the data bus line and its interface electronics illustrated on Figure 1, and also defines the concept of operation and information flow on the multiplex data bus and the electrical and functional formats to be employed.




Figure 1 - Data bus network configuration

1.2 Field of Application

When invoked in a specification or statement of work, these requirements shall apply to the multiplex data bus and associated equipment which is developed either alone or as a portion of a Miniature Mission Store weapon system or subsystem development. The contractor is responsible for invoking all the applicable requirements of this standard on any and all subcontractors he may employ.

2. REFERENCES

2.1 Applicable Documents

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.