m				FEDERAL SUPPL' 5305	Y CLASS	
ш						
	THIS DOCUMENT HAS BEEN DETERMINED TO CONTAIN BASIC AND STABLE TECHNOLOGY WHICH IS NOT DYNAMIC IN NATURE. THIS STANDARD HAS BEEN STABILIZED.					
		STABILIZED	NOTICE			
	THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY THE SAE E-25 GENERAL STANDARDS FOR AEROSPACE AND PROPULSION SYSTEMS COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.					
each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.		SAE values your input. To on this Technical Report, p	provide feedback lease visit al/standards/AS9450B			
each	CUSTODIAN: E-25			PECIFICATION: AS74	55	
SAE reviews	INTERNATIONAL.	AEROSPACE SCREW, MACHINE - STE CADMIUM PLATED, HEX UNS K14675, 195 KSI M	EL, DIFFUSED NICKEL-	\S9450	REV. B	

or written permission of SAE. Tel: 877-606-7323 (inside USA and Carıada) Fax: 724-776-0790 TO PLACE A DOCUMENT ORDER:

Tel: +1 724-776-4970 (outside USA) Email: CustomerService@sae.org SAE WEB ADDRESS: http://www.sae.org

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9450A. THIS SAE STANDARD RETAINS THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL) MAY CONTINUE TO BE MANDATORY FOR DOD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

WARNING

THIS DOCUMENT INCLUDES CADMIUM AS A PLATING MATERIAL. THE USE OF CADMIUM HAS BEEN RESTRICTED AND/OR BANNED FOR USE IN MANY COUNTRIES DUE TO ENVIRONMENTAL AND HEALTH CONCERNS. THE USER SHOULD CONSULT WITH LOCAL OFFICIALS ON THE ENVIRONMENTAL AND HEALTH REGULATIONS REGARDING ITS USE.

	AEROSPACE STANDARD	AS9450 SHEET 1 OF 3	REV. B
INTERNATIONAL	SCREW, MACHINE - STEEL, DIFFUSED NICKEL- CADMIUM PLATED, HEXAGON HEAD, DRILLED, UNS K14675, 195 KSI MIN, .1640-36 UNJF-3A		