

IEC Publication 605-3-5
(First edition - 1996)

Equipment reliability testing -

Part 3: Preferred test conditions -
Section 5: Test cycle 5: Ground mobile equipment -
Low degree of simulation

CORRIGENDUM

Page 31

This technical corrigendum corrects errors inadvertently introduced in drafting and which could lead to incorrect application, found after the circulation of the Final Draft International Standard.

Replace the existing table 6 by the following:

Table 6 - Vibration test severities

Class according to IEC 721-3-5	Duration	Conditions	
		Displacement or acceleration amplitude values according to IEC 68-2-6* or IEC 68-2-64*	Frequency range Hz
5M2	4 sweep cycles	1,5 mm 5 m/s ²	2 to 9 9 to 200
	20 min ¹⁾	1)	1)
5M3	8 sweep cycles	3,5 mm 10 m/s ²	2 to 9 9 to 200
	40 min ²⁾	2)	2)
¹⁾ 0,9 (m/s ²) ² /Hz 10 Hz to 200 Hz ²⁾ 0,36 (m/s ²) ² /Hz 10 Hz to 200 Hz 0,027 (m/s ²) ² /Hz 200 Hz to 500 Hz 0,12 (m/s ²) ² /Hz 200 Hz to 500 Hz			
The above refer to acceleration spectral density.			
* The levels from IEC 721-3-5, table VI, have been reduced since the test cycle is for reliability performance tests and not survivability tests (see clause 1 of this standard).			

March 1996

French text overleaf