INTERNATIONAL STANDARD

ISO 407

Fifth edition 2023-07

Small medical gas cylinders — Pinindex yoke-type valve connections

Petites bouteilles à gaz médicaux — Raccords de robinets du type étrier avec ergots de sécurité





COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Contents Foreword			Page iv
2	-	mative references	
3		ns and definitions	
4	Valv	/e	1
5	Yoke	9	2
6	Basi	ic dimensions	2
	6.1	General	
	6.2	Pin-index yoke-type valve body	
	6.3	Single-pin yoke-type valve connection system	
	6.4	Two-pin yoke-type valve connection system with the pins in a single row	
	6.5	Two-pin yoke-type valve connection system with the pins in a double row	
	6.6	Basic dimensions	5
7		uirements for alternative designs of yoke-type valve connections	
	7.1	Requirements for the design of the connecting yoke	6
	7.2	Examples of alternative construction for the connecting yoke	6
8		ensions and positions of the holes and pins for yoke-type valve connections	
	8.1	General	
	8.2	Outlet connection with single-pin system	
	8.3	Outlet connections with two-pin/single-row system	
		8.3.1 Outlet connection for oxygen	
		8.3.2 Outlet connection for oxygen/carbon dioxide mixture ($CO_2 \le 7 \%$)	11
		8.3.3 Outlet connection for oxygen/helium mixture (He ≤ 80 %)	11
		8.3.4 Outlet connection for ethylene	
		8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off)	12
		8.3.6 Outlet connection for cyclopropane	13
		8.3.7 Outlet connection for helium and for helium/oxygen mixture ($O_2 < 20 \%$)	13
		8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and	1.4
		for carbon dioxide/oxygen mixture (CO ₂ > 7 %)	
		8.3.9 Outlet connection for medical air	
	8.4	Outlet connection with two-nin/double-row system	
	0.4	VIII EL COMBECTION WITH LWO-DIN/UUUDE-LUW SVSLEM	1.7