



Designation: F2461 – 23

Standard Practice for Manufacture, Construction, Operation, and Maintenance of Aquatic Play Equipment¹

This standard is issued under the fixed designation F2461; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers information for manufacture, construction, operations and maintenance of aquatic play equipment and provides safety performance standards for various types of public aquatic play components and aquatic play composite structures.

1.2 Inclusions:

1.2.1 Climbable and climb-resistant aquatic play components, composite aquatic play structures, user controls, water sprays, fountains, and slides that occur on wet decks and wading, swimming or leisure pools. The play components specified herein occur for use in aquatic play areas.

1.2.2 Play equipment, fall zones, use zones for wet decks, wading pools, swimming pools and leisure pools.

1.2.3 This standard is intended to apply to Aquatic Play Equipment that is located in and around re-circulated and potable water recreational facilities. Such facilities include but are not limited to amusement parks, theme parks, water parks, family entertainment centers, municipal swimming pools and municipal parks.

1.2.4 Waterslides 6 ft in height or smaller.

1.3 Exclusions:

1.3.1 Playground equipment that does not have an entry or an exit onto or into a wet deck, wading pool, swimming pool or aquatic recreation pool.

1.3.2 Home playground or home pool equipment or play equipment as scoped in Consumer Safety Performance Specification F1148-21 and ANSI/NSPI-5.

1.3.3 Waterslides as scoped in Practice F2376-22.

1.3.4 Flotation devices used on water slides or in swimming pools.

1.3.5 Swimming pools as specified by ANSI/NSPI-1 or ANSI/IAF-9.

1.3.6 Products or facility elements specifically designed to provide access to and from pools for people with disabilities.

1.3.7 Water rides such as log flumes, raft rides, inner tube rides, waterslides or other attractions where the participant sits in a vehicle or is physically propelled or moved by or with water.

1.3.8 Sports equipment, fitness equipment, and diving equipment.

1.4 Compliance:

1.4.1 Where water is indirectly or directly added or applied to Consumer Safety Performance Specification F1487-21 play equipment, the equipment shall comply with this standard. Where a requirement for compliance to a section of the Consumer Safety Performance Specification F1487-21 standard is required by this standard, the section number is preceded with the standard's designation.

1.4.2 Soft contained play structures with aquatic play components shall comply with Safety Performance Specification F1918-21 except as modified by this standard.

1.4.3 Aquatic play components and composite play structures represented, as complying with this safety performance standard shall meet all applicable requirements specified herein. Anyone representing compliance with this standard shall keep such essential records as are necessary to document any claim that the requirements within this standard have been met.

1.5 This standard includes the following sections:

Scope	Section 1
Referenced Documents	Section 2
Terminology	Section 3
Manufacturing and Materials	Section 4
Design	Section 5
Performance Requirements	Section 6
Operator Responsibilities	Section 7
Manufacturer/Designer Responsibilities	Section 8
Installer Responsibilities	Section 9

1.6 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard. (The conversion factor from inch-pound to metric units is 1 in. = 25.4 mm, and 1 lb = 4.4482 N.)

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the*

¹ This practice is under the jurisdiction of ASTM Committee F24 on Amusement Rides and Devices and is the direct responsibility of Subcommittee F24.70 on Water Related Amusement Rides and Devices.

Current edition approved June 15, 2023. Published August 2023. Originally approved in 2009. Last previous edition approved in 2020 as F2461 – 20a. DOI: 10.1520/F2461-23.

responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.8 This international standard was developed in accordance with internationally recognized principles on standardization established in the *Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee*.

2. Referenced Documents

2.1 ASTM Standards:²

F770 Practice for Ownership, Operation, Maintenance, and Inspection of Amusement Rides and Devices

F1148 Consumer Safety Performance Specification for Home Playground Equipment

F1193 Practice for Quality, Manufacture, and Construction of Amusement Rides and Devices

F1292 Specification for Impact Attenuation of Surfacing Materials Within the Use Zone of Playground Equipment

F1487 Consumer Safety Performance Specification for Playground Equipment for Public Use

F1918 Safety Performance Specification for Soft Contained Play Equipment

F2291 Practice for Design of Amusement Rides and Devices

F2376 Practice for Classification, Design, Manufacture, Construction, and Operation of Water Slide Systems

F2974 Practice for Auditing Amusement Rides and Devices

2.2 ANSI Standards:³

ICC/ANSI A117.1 Accessible and Usable Buildings and Facilities

ANSI A10.11 Personal and Debris Nets

ANSI/IAF-9 American National Standard for Aquatic Recreation Facilities

ANSI/NSPI-1 American National Standard for Public Swimming Pools

ANSI/NSPI-5 American National Standard for Residential Inground Swimming Pools

2.3 Other Standards:

NFPA 70 National Electric Code (NEC)⁴

OSHA Subpart D 1910.28 Duty to have fall protection and falling object protection⁵

3. Terminology

3.1 Reserved for future inclusions.

4. Manufacturing and Materials

4.1 Aquatic play components shall comply with Consumer Safety Performance Specification **F1487-21** Section 4 except as modified by this standard.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

⁴ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

⁵ Available from Occupational Safety and Health Administration (OSHA), 200 Constitution Ave., NW, Washington, DC 20210, <http://www.osha.gov>.

4.2 *Durability*—Aquatic play components and composite play systems shall be manufactured and constructed only of materials that have a demonstrated durability in the aquatic playground, swimming pool or similar setting.

4.2.1 Any new materials shall have documented performance and material properties or tested accordingly for durability by the equipment manufacturer.

4.3 *Compatibility*—Materials used in the manufacture of aquatic play components shall not create an unsanitary or toxic condition for users and the aquatic environment in which they are installed.

4.4 Materials:

4.4.1 *Metals*—Refer to Consumer Safety Performance Specification **F1487-21**, Sections 4.1.1 and 4.1.2.

4.4.2 *Plastics*—Refer to Consumer Safety Performance Specification **F1487-21**, Section 4.1.1.

4.4.3 *Wood*—Refer to Consumer Safety Performance Specification **F1487-21**, Sections 4.1.1 and 4.1.3.

4.4.4 *Concrete*—Concrete footings and slabs shall comply with local jurisdiction or equal to the requirements of the International Building Code.

4.4.5 *Foam*—Foam materials used in aquatic play components shall be skinned or of a closed cell type. Foam materials that are subject to ultraviolet (UV) degradation shall be protected against ultraviolet light or include ultraviolet degradation inhibitors. Foam products shall not leach any chemicals that could affect water chemistry.

4.4.6 Automotive or industrial tires are not permitted in the aquatic play environment.

4.5 Components:

4.5.1 *Netting*—Netting material for structural purpose, subject to UV degradation, shall be protected from U/V exposure or include U/V degradation inhibitors.

4.5.2 *Fasteners and Cables*—Fasteners are required to comply with Practice **F2291-22a**, Section 16 and also Consumer Safety Performance Specification **F1487-21** Section 4.2.1 to Section 4.2.4 inclusive.

4.5.2.1 Fasteners in aquatic play components when located on walking, stepping, sitting and sliding surfaces of aquatic play components and wet decks shall be flush, and without any sharp or abrasive finish.

4.5.2.2 All fasteners used to construct Aquatic Play Equipment shall be maintained and consistent as specified by the manufacturer.

4.5.2.3 All fasteners, connecting, and covering devices shall be corrosion resistant or be provided with a corrosion-resistant coating.

4.5.2.4 When installed in accordance with the manufacturer's specifications, fasteners, connecting, and covering devices shall not loosen or be removable without the use of tools.

4.5.2.5 Hardware in moving joints shall also be secured against unintentional loosening.

4.5.2.6 Moving suspended elements shall be connected to the fixed support with bearings or bearing surfaces that serve to reduce friction or wear.

4.5.2.7 Steel cable that is permanently affixed to a hanger assembly performs as a bearing surface. Cable ends shall be

inaccessible or capped to prevent injury from frayed wires. Cables and steel-cored ropes should be protected to prevent fraying, loosening, unraveling, or excessive shifting of joints.

4.5.3 *Electrical Components*—Electrical components that require power to operate, should be installed with the materials, voltage and grounding requirements as required by local governing authorities and NFPA 70.

4.5.4 Coatings shall comply with Consumer Safety Performance Specification F1487-21, Section 4.1.

4.5.5 Replacement Parts for Aquatic Play Equipment shall be:

4.5.5.1 Procured from the original manufacturer of the aquatic play equipment, using the appropriate manufacturer-supplied identifying nomenclature; or

4.5.5.2 Procured or produced to meet or exceed the manufacturer's minimum specification.

5. Design

5.1 Load Calculations:

5.1.1 *Slide Beds*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.4.1.4.

5.1.2 *Loading Test Criteria*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.2.

5.1.3 *Components and Structures Subjected to Vertical Loads*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.4 through Section 12.4.1.1 inclusive.

5.1.4 *Structures Containing Two or More Longitudinal Components*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.4.1.2.

5.1.5 *Individual Surfaces*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.4.1.3.

5.1.6 *Components with Designated Occupancy*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.4.1.5.

5.1.7 *Components Subjected to Lateral Loads*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.5 through Section 12.5.2 inclusive.

5.1.8 *Alternative Testing for Structural Integrity*—Refer to Consumer Safety Performance Specification F1487-21, Section 12.6.

5.2 Structural Design:

5.2.1 Structural integrity tests shall be conducted by manufacturers as per Practice F2291-22a, Section 8.6 through 8.16 inclusive.

5.2.1.1 In multi-level, composite play structures provide lateral sway brace loads of 24 lb per ft (350 N/m) parallel and 10 lb per ft (145.9 N/m) perpendicular to the floor or platform level.

5.2.1.2 *Wind Load*—For structures with elevated platforms where the height of the platform is larger than the width or depth of the elevated platform, the composite structure shall be designed to withstand 100 mph wind (3 s gust) for non-operational conditions. The calculation shall take into account roofs, dump buckets, awnings, flags, banners, or any other element that may affect the wind load calculations.

5.2.1.3 Structural calculations shall consider the combination of loads corresponding to foreseeable severe conditions.

5.2.2 *Platforms, Walking or Climbing Surfaces*—Structural engineering of composite play structure platforms with 20 % slope or less shall be based upon a live load as per Practice F2291-22a, Section 8.15 and occupancy of 3 ft² per person.

5.2.3 Stairs, Guardrails, and Handrails:

5.2.3.1 Guardrails shall be designed to comply with Practice F2291-22a Section 14, with the exception that the maximum opening size shall reject a torso probe as specified in Consumer Safety Performance Specification F1487-21 Fig A1.2 (see Appendix X2).

5.2.3.2 Stairs and handrails shall be designed to comply with Practice F2291-22a Section 14.

5.2.4 Netting Reserved for future.

5.2.5 For the purposes of calculations, the water load on an aquatic play component surfaces other than water slides shall be designed to the amount of live load on an aquatic play component or other surfaces of the composite play structure. Where used, Design/Engineers shall consider impact and dynamic loads such as water bucket dumps, and shall be included in the live loading design of structures, platforms and roofs.

5.2.6 Overhead play elements. Overhead climbing elements shall be designed to withstand a 200-lb (890 N) per lineal foot live load. Their mounting and connectors shall be designed to accommodate the total live loading of the free spanned element.

5.3 *Access and Egress*—Aquatic play components shall comply with Consumer Safety Performance Specification F1487-21 Section 6 and 7 except as provided herein.

5.3.1 Composite play structures utilizing multiple aquatic play components are permitted in wet decks, wading pools and as a means of access to a pool when it conforms to the requirements of Consumer Safety Performance Specification F1487-21 Sections 9.7 and 9.8 and the requirements of this standard.

5.3.2 Unenclosed level, stair or ramp entries are permitted.

5.3.3 Unless otherwise specified herein, aquatic play components are permitted to be accessed to and from wet decks and from the perimeter of or from within wading pools, swimming pools or leisure pools.

5.3.4 All means of entry and egress shall be slip resistant.

5.3.5 Access to and from composite play structures and soft contained play systems is permitted from pool decks, wet decks and from inside the pool.

5.4 *Climb Resistance*—The following are climb-resistant under this standard:

5.4.1 Aquatic play components that lack a designated play surface or handgrips, or both, within 84 in. of the ground or deck.

5.4.2 Equipment flush with the play surface. Protrusions from play surfaces shall not exceed VA thickness and shall have rounded, radiused, or angular edges to prevent hand and foot holds.

5.4.3 Horizontal or angled members 60 in. (1625 mm) or more above the ground or deck surface.

5.4.4 Slanted members with more than 30° slope from horizontal.