



SURFACE VEHICLE STANDARD

J514™-3

DEC2023

Issued 2022-06
Revised 2023-12

Superseding J514-3 JUN2022

Metallic Connections for Fluid Power and General Use - Part 3: NPTF Pipe Adapters and NPSM Adapter Unions

RATIONALE

Revise Tables 6 and 11 to remove references to tube size. Dash size designation for SAE J1926-3 stud ends were also added to Table 11 for clarity.

FOREWORD

The January 2012 edition of SAE J514 was a single document specifying the requirements for the following:

- 37 degree flare adapters with SAE J1926-3 stud ends and NPTF pipe ends.
- Flareless bite type adapters with SAE J1926-3 stud ends and NPTF pipe ends.
- O-ring plugs with internal and external hex.
- NPTF pipe adapters.
- 30 degree NPSM adapter unions.

SAE J514-3 specifies NPTF adapters and 30 degree NPSM adapter unions. Formerly, SAE J514 was organized as a single document with ten clauses, which included six sections. SAE J514 has been organized into three sections as follows:

Part 1: 37 degree flared fittings.

Part 2: Flareless (bite type) fittings.

Part 3: NPTF pipe fittings and pipe unions.

It is important to note that this and all SAE J documents are intended for ground vehicle use only and are not intended for aerospace vehicles.

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2023 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

For more information on this standard, visit
https://www.sae.org/standards/content/J514/3_202312

SAE WEB ADDRESS:
<http://www.sae.org>

TABLE OF CONTENTS

1.	SCOPE	4
2.	REFERENCES	4
2.1	Applicable Documents	4
2.1.1	SAE Publications	4
2.1.2	ANSI Accredited Publications	4
2.1.3	ASME Publications	4
2.1.4	ASTM Publications	5
2.1.5	ISO Publications	5
3.	DEFINITIONS	5
4.	REQUIREMENTS - GENERAL SPECIFICATIONS	6
4.1	Size Designations	6
4.2	Dimensions and Tolerances	7
4.3	Passages	8
4.4	Wall Thickness	8
4.5	Contour	8
4.6	Pipe Threads	8
4.7	Material	10
4.8	Corrosion Protection	10
4.9	Workmanship	10
5.	PERFORMANCE REQUIREMENTS	10
5.1	Working, Proof, and Burst Pressure	11
5.2	Proof Test	11
5.3	Burst Test	11
5.4	Cyclic Endurance (Impulse) Test	11
5.5	Test Data Form	11
6.	PACKAGING AND MARKING	12
6.1	Marking	12
6.2	Protection	12
6.3	SAE J846 Ordering Designation, Part Identification Number (PIN)	12
7.	ADAPTER UNIONS	20
8.	NOTES	25
8.1	Identification Statement and Procurement Information	25
8.2	Revision Indicator	25
Figure 1	Run and branch illustration	6
Figure 2	Hex tolerances	7
Figure 3	Hexagon pipe nipple (140137)	12
Figure 4	Hexagon pipe coupling (140138)	12
Figure 5	Adapter (140139)	13
Figure 6	Increase adapters (140139)	13
Figure 7	Reducer bushings (140140)	13
Figure 8	90 degree pipe elbow (140238)	15
Figure 9	45 degree pipe elbow (140338)	15
Figure 10	90 degree street elbow (140239)	15
Figure 11	45 degree street elbow (140339)	15
Figure 12	Pipe tee internal, external, internal (140424)	16
Figure 13	Pipe tee internal, internal, external (14025)	16
Figure 14	Pipe tee internal, internal, internal (140438)	16
Figure 15	90 degree pipe elbow (140238)	16
Figure 16	45 degree pipe elbow (140338)	17
Figure 17	90 degree street elbow (140239)	17
Figure 18	45 degree street elbow (140339)	17

Figure 19	Pipe tee internal, external, internal (140424)	17
Figure 20	Pipe tee internal, internal, external (140425)	18
Figure 21	Pipe tee internal, internal, internal (140438)	18
Figure 22	Female adapter union to male pipe (140130).....	20
Figure 23	45 degree female adapter union to male pipe (140330).....	20
Figure 24	90 degree female adapter union to male pipe (140230).....	20
Figure 25	Female adapter union to female pipe (140131).....	21
Figure 26	45 degree female adapter union to female pipe (140331).....	21
Figure 27	90 degree female adapter union to female pipe (140231)	21
Figure 28	Female adapter union to male straight thread (140157).....	21
Figure 29	45 degree female adapter union to adj. male straight thread (140357).....	22
Figure 30	90 degree female adapter union to adj. male straight thread (140257).....	22
Table 1A	Hex tolerances	7
Table 1B	Hole tolerances	7
Table 2	Linear tolerances (except for broken edges).....	7
Table 3	Broken edges tolerances (external radii and chamfer heights).....	8
Table 4	Angular tolerances	8
Table 5	Pipe thread chamfer diameters.....	9
Table 6	Working pressure ratings ⁽¹⁾ capable of 4-to-1 minimum burst	11
Table 7	Dimensions of hexagon pipe nipples (Figure 3)	12
Table 8	Dimensions of hexagon pipe coupling (Figure 4)	13
Table 9	Dimensions of adapters, increase adapters, and reducer bushings (Figures 5, 6, and 7).....	14
Table 10	Dimensions of forged and barstock types of pipe elbows, street elbows, and pipe tees (Figures 8 to 21).....	19
Table 11	Dimensions of adapter unions (Figures 22 through 30).....	23
Table 12	Minimum stock size for female pipe ends	25
Table 13	Minimum stock size for male pipe ends	25