



# Standard Specification for Ovens, Microwave, Electric<sup>1</sup>

This standard is issued under the fixed designation F1360; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

## 1. Scope

1.1 This specification covers commercial microwave ovens. These ovens use ultrahigh frequency electromagnetic radiation in the approved industrial, scientific, and medical bands to defrost, heat, and cook food.

1.2 *Limitations*—This specification does not include all types, sizes, groups, styles, and classes of the commodities indicated by the titles of the specification, or that are commercially available, but is intended to cover the types, sizes, groups, styles, and classes that are suitable for general requirements.

1.3 *Oven Selection And Application*—Prior to the use of the classifications given in 4.1, the user agency should ensure they are not restricted by some aspect of the microwave oven design such as a weight or external dimension limitation that would prevent the unrestricted use of the classifications given in 4.1.

1.4 *Microwave Oven Availability*—Although 4.1 lists a wide range of sizes, classes, groups, and styles for commercial types of ovens, not all combinations are available.

1.5 The values stated in inch-pound units are to be regarded as the standard. The SI units given in parentheses are for information only.

1.6 The following precautionary caveat pertains to the test method portion only, Section 10, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.7 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee F26 on Food Service Equipment and is the direct responsibility of Subcommittee F26.02 on Cooking and Warming Equipment.

Current edition approved Feb. 1, 2024. Published March 2024. Originally approved in 1991. Last previous edition approved in 2023 as F1360 – 17 (2023). DOI: 10.1520/F1360-24.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

A176 Specification for Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip (Withdrawn 2015)<sup>3</sup>

A240/A240M Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications

B108 Specification for Aluminum-Alloy Permanent Mold Castings

B209 Specification for Aluminum and Aluminum-Alloy Sheet and Plate (Metric) B0209\_B0209M

D3951 Practice for Commercial Packaging

F760 Specification for Food Service Equipment Manuals

F1166 Practice for Human Engineering Design for Marine Systems, Equipment, and Facilities

F1317 Test Method for Calibration of Microwave Ovens

### 2.2 ANSI Standards:<sup>4</sup>

B1.1 Unified Inch Screw Threads (UN and UNR Thread Form)

C62.41 Guide for Surge Voltages in Low Voltage AC-Power Circuits<sup>4</sup>

WD-6 Wiring Devices—Dimensional Requirements<sup>4</sup>

Z1.4 Sampling Procedures and Tables for Inspection by Attributes<sup>4</sup>

2.3 *International Electrotechnical Commission Standard:*<sup>4</sup>  
Standard No. 705 Methods for Measuring the Performance of Microwave Ovens for Household and Similar Purposes

2.4 *National Sanitation Foundation Standard:*<sup>5</sup>

NSF/ANSI 4 Commercial Cooking, Rethermalization, and Powered Hot Food Holding and Transport Equipment

2.5 *Underwriters Laboratories Standard:*<sup>6</sup>  
ANSI/UL 923 for Microwave Cooking Appliances

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on www.astm.org.

<sup>4</sup> Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

<sup>5</sup> Available from NSF International, P.O. Box 130140, 789 N. Dixboro Rd., Ann Arbor, MI 48113-0140.

<sup>6</sup> Available from Underwriters Laboratories (UL) LLC, Corporate Progress, 333 Pfingsten Rd., Northbrook, IL 60062.

2.6 *Federal Standard*:<sup>7</sup>

**FED-STD-123** Marking for Shipment (Civil Agencies)

2.7 *Military Standards*:<sup>7</sup>

**MIL-STD-167-1** Mechanical Vibrations of Shipboard Equipment

**MIL-STD-461** Requirements For the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment

**MIL-E-1399/300** Interface Standard for Shipboard Systems, Section 300A, Electric Power, Alternating Current

2.8 *Federal Regulations*:<sup>8</sup>

**Title 21, Food and Drugs, Subchapter J—Radiological Health**

**Title 29, Labor, Chapter 17, Occupational Safety and Health Administration, Department of Labor**

### 3. Terminology

3.1 *Definitions of Terms Specific to This Standard*:

3.1.1 *cavity*—that portion of the microwave cooking appliance in which food may be heated, cooked, or defrosted.

3.1.2 *door*—the moveable barrier that permits access to the cavity for placement or removal of food, and whose function is to prevent emission of microwave energy from the passage or opening that provides access to the cavity.

3.1.3 *interlock*—a device or system, either electrical, mechanical, or electromechanical, that serves to prevent exposure to an electric shock, or physical injury, or excessive radiation emission when a door, cover, or access panel is opened or removed.

3.1.4 *magnetron*—a type of microwave energy generator usually used in microwave cooking appliances.

3.1.5 *microwave oven*—a device that uses ultrahigh frequency electromagnetic radiation in the bands of  $915 \pm 25$  and  $2450 \pm 50$  MHz to prepare food.

3.1.6 *microwave radiation emission*—the microwave energy to which persons might be exposed during operation or user servicing of a microwave cooking appliance.

3.1.7 *viewing screen*—that feature of a microwave appliance, usually part of the door assembly, that is opaque to microwave energy but visually transparent to provide for viewing the oven contents.

### 4. Classification

4.1 Microwave ovens covered by this specification are classified by types, sizes, groups, styles, and classes as follows:

4.1.1 *Type*:

4.1.1.1 *Type I*—Commercial microwave oven.

4.1.1.2 *Type II*—Combination commercial microwave and convection/radiant heat oven.

4.1.2 *Size*:

4.1.2.1 *Size 600*—600 to 1199 W microwave power output.

4.1.2.2 *Size 1200*—1200 to 1799 W microwave power output.

4.1.2.3 *Size 1800*—1800 and greater watt microwave power output.

4.1.3 *Group*:

4.1.3.1 *Group 1*—0.5 to 0.8 ft<sup>3</sup> (0.014 m<sup>3</sup> to 0.0226 m<sup>3</sup>) cooking cavity (minimum cooking cavity dimensions of 7.5 shall be met).

4.1.3.2 *Group 2*—Over 0.8 to 1.2 ft<sup>3</sup> (0.0226 m<sup>3</sup> to 0.034 m<sup>3</sup>) cooking cavity.

4.1.3.3 *Group 3*—Over 1.2 to 1.5 ft<sup>3</sup> (0.034 m<sup>3</sup> to 0.042 m<sup>3</sup>) cooking cavity.

4.1.3.4 *Group 4*—Over 1.5 ft<sup>3</sup> (0.042 m<sup>3</sup>) cooking cavity.

4.1.4 *Style*:

4.1.4.1 *Style 1*—Dial type timer(s).

4.1.4.2 *Style 2*—Digital timer and touchpad controls (computer controlled).

4.1.4.3 *Style 3*—Dial or pushbutton timer(s), or both.

4.1.5 *Class*:

4.1.5.1 *Class 1*—208 V, 60 Hz, 1 phase.

4.1.5.2 *Class 2*—208 V, 60 Hz, 3 phase.

4.1.5.3 *Class 3*—240 V, 60 Hz, 1 phase.

4.1.5.4 *Class 4*—240 V, 60 Hz, 3 phase.

4.1.5.5 *Class 5*—120 V, 60 Hz, 1 phase.

4.1.5.6 *Class 6*—220 V, 60 Hz, 3 phase.

4.1.5.7 *Class 7*—230 V, 50 Hz, 1 phase.

4.1.5.8 *Class 8*—230 V, 50 Hz, 3 phase.

### 5. Ordering Information

5.1 *Ordering Data*—Purchasers shall select the preferred options permitted herein and include the following information in procurement documents:

5.1.1 Title, number, and date of this specification,

5.1.2 Type, size, group, class, and style of oven required (see 1.2 and 4.1),

5.1.3 When oven accessories, colors, hardware, fittings, door, cooking cavity, and exterior materials are other than as specified (see 6.2, 6.4, 6.5, and 6.6),

5.1.4 When an automatic oven shutdown is required for vending operation use,

5.1.5 When surge voltage protection is required (see 7.4.2),

5.1.6 When an air intake filter is required (see 7.6),

5.1.7 When a heat control is to be provided (see 7.7),

5.1.8 When convection heating capability is to be provided (see 7.7),

5.1.9 When a temperature sensing probe is to be provided (see 7.7),

5.1.10 When an infrared temperature sensing device is to be provided (see 7.7),

5.1.11 When power level controls are to be other than specified, or when selection of microwave power in 10 % increments is offered (see 7.7.2),

5.1.12 Voltage and frequency (Hz) of input power, if other than specified (see 7.8.1),

5.1.13 When the power cord length is other than specified (see 7.8.2),

<sup>7</sup> Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, or Acquisition Streamlining and Standardization Information System (ASSIST), which is the official source of all documents listed in the DoD Index of Specifications and Standards. The ASSIST can be located at <http://dsp.dla.mil>.

<sup>8</sup> Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401.

5.1.14 Treatment and painting, if other than specified (see 7.9),

5.1.15 When windows are required in oven doors (see 7.11),

5.1.16 When a mounting is required for the oven (see 8.1).

5.1.17 When a cavity light for ovens without viewing screens is other than specified,

5.1.18 When the contractor is to have responsibility for, and use facilities other than specified for inspection requirements,

5.1.19 When a first article is required for inspection and approval,

5.1.20 When an oven light is required to be on,

5.1.21 Level of preservation and packing required if other than as stated in Practice D3951 (see 12.1),

5.1.22 When sides of shipping containers are to be marked other than as specified (see 12.2),

5.1.23 When Federal/Military procurements are required, review and implement the applicable supplemental requirements (see S1.1 thru S7.2.3),

5.1.24 When specified in the purchase order or contract, the purchaser shall be furnished certification that samples representing each lot have been either tested or inspected as directed in this specification and the requirements have been met. When specified in the purchase order or contract, a report of the test results shall be furnished.

## 6. Materials

6.1 *General*—Microwave ovens shall conform to the referenced documents listed in Section 2. Materials used shall be free from defects that would affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term “recovered materials” means materials that have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

6.2 *Hardware and Fittings*—Unless otherwise specified (see 5.1), all hardware and fittings shall be corrosion-resistant or suitably processed to resist corrosion in accordance with the manufacturer’s standard practice.

6.3 *Threaded Parts*—All threaded parts shall conform to ANSI B1.1.

6.4 *Cooking Cavity*—Unless otherwise specified (see 5.1), the cooking cavity shall be constructed of Types 302, 304, or 316 corrosion-resistant steel conforming to Specification A240/A240M, or aluminum alloy Type 3003-0 conforming to Specification B209. The cooking cavity shall be constructed and sealed to prevent spillage from draining into the oven chassis.

6.5 *Door*—Unless otherwise specified (see 5.1), the door shall be constructed of Types 302 or 304 corrosion-resistant

steel conforming to Specification A240/A240M. Aluminum alloy Types 356 or 319 conforming to Specification B108 or Type 6061 aluminum alloy conforming to Specification B209 may also be used alone or in combination with the corrosion-resistant steel described.

6.6 *Exterior*—Unless otherwise specified (see 5.1), material shall be Types 302, 304, 316 or 430 corrosion-resistant steel conforming to Specifications A240/A240M or A176 as applicable, and thickness shall be 20 gage min. (0.0375 in. (1 mm) U.S. revised standard gage).

## 7. Design, Construction, and Physical Requirements

7.1 *General*—Microwave ovens shall conform to the referenced documents listed in Section 2. The oven shall be delivered assembled with all components necessary to ensure a fully functional product.

7.2 *Microwave Energy Source*—Microwave energy shall be generated using one or more magnetron tubes or any other suitable generating source of microwave energy. Microwave energy shall be interrupted by an interlock system and the generating source shall be rendered inoperative (either turned off or switched to a standby mode) when the oven door is open or not securely latched in the closed position.

7.2.1 *Warning Label*—A warning marking shall be affixed to the outer case assembly or adjacent to each service access cover and adjacent to one of the fasteners that secures the outer case assembly to the oven chassis. A high voltage warning label shall also be placed near the high voltage components inside the outer case. The label shall include but is not limited to the following warnings:

7.2.1.1 A warning of high voltage,

7.2.1.2 Power supply must be disconnected before servicing,

7.2.1.3 Access covers must be in place during use, and

7.2.1.4 Servicing should be done only by authorized individuals.

7.2.2 *Microwave Radiation Distribution*—Means shall be provided to maintain uniform distribution of microwave radiation throughout the cooking cavity.

7.2.3 *Door Mechanism*—The mechanical door latch mechanism shall be certified to be operable for no fewer than 200 000 cycles without any visible deformation or inoperation.

7.3 *Magnetron Protection:*

7.3.1 *Reflected Energy*—With the oven empty except for any required tray or sheet furnished by the manufacturer, the oven shall be capable of operation at maximum power output for 1 h or one maximum timer cycle, whichever is shorter, without damage to the magnetron or other oven components.

7.3.2 *Thermal Protection*—Means shall be provided to protect the magnetron from damage due to excessive heating. Protective devices shall be automatically resettable, or manually resettable without requiring any disassembly of the oven.

7.4 *Circuit Protection:*

7.4.1 *Excess Current Draw*—The power supply shall be protected against any damage that would occur as a result of an