



BSI Standards Publication

# Full ring ovalization test for determining the susceptibility to cracking of linepipe steels in sour service – Test method

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2016

Published by BSI Standards Limited 2016

ISBN 978 0 580 89474 9

ICS 77.060

The following BSI references relate to the work on this document:

Committee reference PSE/17

Draft for comment 16/30319903 DC

**Publication history**

First published June 2016

**Amendments issued since publication**

Date	Text affected
------	---------------

---

## Contents

Foreword *iii*

Introduction 1

- 1 Scope 1
- 2 Normative references 2
- 3 Terms and definitions 2
- 4 Principle 5
- 5 Reagents 5
- 6 Apparatus 6
- 7 Samples 6
- 8 Surface preparation 7
- 9 Procedure for test specimens with internal loading 7
- 10 Expression of results 12

### Annexes

- Annex A (normative) Ultrasonic examination of pipe, plate and welds during accelerated laboratory tests 13
  - Annex B (normative) Ring loading 17
  - Annex C (informative) Typical internal and external load application rigs for use in the full ring test 27
  - Annex D (normative) Chemistry of test solutions 28
  - Annex E (informative) Analysis of test solution – iodimetric titration procedure 29
  - Annex F (informative) Illustrated summary of the full ring test procedure 30
  - Annex G (informative) Hydrogen sulfide (H<sub>2</sub>S) health and safety considerations 38
  - Annex H (informative) Sample identification and test record, Form 1 39
  - Annex I (informative) Sample identification and test record, Form 2 40
  - Annex J (informative) Acceptance criteria 43
  - Annex K (informative) Sulfide stress corrosion (SSC) and hydrogen induced cracking (HIC) 43
  - Annex L (informative) Explanatory notes on test method: Galvanic Coupling 45
  - Annex M (informative) Modified test procedure for externally loaded test specimens (Diameter <12 in. [305 mm]) 45
  - Annex N (informative) Magnetic particular inspection (MPI) procedure 46
- Bibliography 47

### List of figures

- Figure 1 – Full ring test using internal loading techniques 8
- Figure 2 – Modified full ring test using external loading technique 8
- Figure A.1 – Most common crack locations 13
- Figure B.1 – Gauge positions for seamless ring specimens 20
- Figure B.2 – Gauge positions for ring specimens that contain only a longitudinal seam weld 21
- Figure B.3 – Gauge positions on specimens having a spirally wound seam only 22
- Figure B.4 – Gauge positions for ring specimens that contain only a girth weld seam 22
- Figure B.5 – Gauge positions for ring specimens that contain both circumferential and longitudinal weld seams and have an angular gap of between 5° and 175° between longitudinal seams 23
- Figure B.6 – Modified gauge positions for ring specimens that contain both circumferential and longitudinal weld seams and have an angular off-set of <5° or 175° to 185° between longitudinal weld seams 24
- Figure B.7 – Gauge positions on specimens having spirally wound weld seams combined with a girth weld 24