

AEROSPACE MATERIAL SPECIFICATION

SAE.

AMS 2750D

Issued Revised APR 1980 SEP 2005

Superseding AMS 2750C

(R)

PYROMETRY

1. SCOPE:

- 1.1 This specification covers pyrometric requirements for thermal processing equipment used for heat treatment. It covers temperature sensors, instrumentation, thermal processing equipment, system accuracy tests, and temperature uniformity surveys. These are necessary to ensure that parts or raw materials are heat treated in accordance with the applicable specification(s).
- 1.2 This specification is not applicable to heating, or to intermediate thermal processing unless specifically referenced by a material or process specification.
- 1.3 This specification applies to laboratory furnaces to the extent specified in 3.6.

2. APPLICABLE DOCUMENTS:

The issue of the following documents in effect on the date of the purchase order forms a part of this specification to the extent specified herein. The supplier may work to a subsequent revision of a document unless a specific document issue is specified. When the referenced document has been canceled and no superseding document has been specified, the last published issue of that document shall apply.

2.1 ASTM Publications:

Available from ASTM, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959 or www.astm.org.

| ASTM E 207 | Thermal EMF Test of Single Thermoelement Materials by Comparison with a |
|--------------------|--|
| | Reference Thermoelement of Similar EMF-Temperature Properties |
| ASTM E 220 | Calibration of Thermocouples by Comparison Techniques |
| ASTM E 230 | Standard Specification and Temperature-Electromotive Force (EF) Tables for |
| | Standardized Thermocouples |
| ASTM E 608 | Mineral-Insulated, Metal-Sheathed Base Metal Thermocouples |
| ASTM E 1129 | Standard Specification for Thermocouple Connectors |
| ASTM MNL 7 | Presentation of Data and Control Chart Analysis |
| ASTM MNL 12 | Use of Thermocouples in Temperature Measurement |

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this Report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions. Copyright 2005 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 724-776-4970 (outside USA) Fax: 724-776-0790 Tel: 877-606-7323 (inside USA and Canada)



Email: custsvc@sae.org

3. TECHNICAL REQUIREMENTS

CONTENTS

| Section | Topic | Page |
|-----------|---|------|
| 3.1 | Temperature Sensors | 4 |
| 3.1.1 | General Sensor Information | 4 |
| 3.1.1.1 | Sensor Certificate of Compliance Requirements | 4 |
| 3.1.1.2 | Degrees to Millivolt Conversion | 4 |
| 3.1.1.3 | Thermocouple Calibration Requirements | 4 |
| 3.1.1.4 | Thermocouple Usage | 5 |
| 3.1.1.5 | Extension Wire | 5 |
| 3.1.1.6 | Wire Rolls - Calibration Requirements | 5 |
| 3.1.1.7 | Wire Rolls – Maximum Allowable Length | 6 |
| 3.1.1.8 | Reuse of Type K and E thermocouples as Secondary Standards or | |
| | SAT Sensors | 6 |
| 3.1.1.10 | Expendable Base-Metal Test Thermocouple "U" Formula | 6 |
| 3.1.2 | Reference Standard Sensors | 6 |
| 3.1.3 | Primary Standard Sensors | 6 |
| 3.1.4 | Secondary Standard Sensors | 6 |
| 3.1.5 | Temperature Uniformity Survey Sensors | 6 |
| 3.1.6 | System Accuracy Test Sensors | 7 |
| 3.1.7 | Control, Monitoring, and Recording Sensors | 7 |
| 3.1.8 | Load Sensors | 7 |
| 3.2 | Instrumentation | 8 |
| 3.2.4 | Controlling, Monitoring or Recording Instruments | 9 |
| 3.2.5 | Instrument Calibration (also see Table 3) | 9 |
| 3.2.6 | Instrumentation Records | 10 |
| 3.2.7 | Electronic Records – Instrumentation | 11 |
| 3.3 | Thermal Processing Equipment | 11 |
| 3.3.1 | Furnace Classes (also see Tables 6 and 7) | 11 |
| 3.3.1.1 | Instrumentation Type A | 12 |
| 3.3.1.2 | Instrumentation Type B | 12 |
| 3.3.1.3 | Instrumentation Type C | 12 |
| 3.3.1.4 | Instrumentation Type D | 13 |
| 3.3.1.5 | Instrumentation Type E | 13 |
| 3.3.1.6.1 | Instrumentation - Refrigeration Equipment | 13 |
| 3.3.1.6.2 | Instrumentation - Quench Systems | 13 |
| 3.4 | System Accuracy Tests (SAT's) | 13 |
| 3.4.2 | System Accuracy Test Frequency (also see Tables 6 and 7) | 14 |
| 3.4.3 | System Accuracy Test Waiver | 14 |
| 3.4.4 | System Accuracy Test Procedure | 15 |
| 3.4.4.2.1 | Resident Test Sensors | 15 |
| 3.4.4.8 | Alternative System Accuracy Test Procedure | 18 |
| 30 | | |

CONTENTS

| Section | Topic | Page |
|----------|---|------|
| 3.4.5 | System Accuracy Test Instrumentation (also see Tables 1 and 3) | 18 |
| 3.4.6 | Records – System Accuracy Test | 18 |
| 3.5 | Furnace Temperature Uniformity Surveys (TUS) | 18 |
| 3.5.2 | Multiple Qualified Operating Temperature Ranges | 19 |
| 3.5.5 | Initial TUS Temperatures | 20 |
| 3.5.6 | Periodic TUS Temperatures | 20 |
| 3.5.7 | TUS Frequency (also see Tables 8 and 9) | 20 |
| 3.5.8 | Furnace Parameters During TUS | 20 |
| 3.5.9 | Furnace Temperature at Insertion of TUS Sensors | 20 |
| 3.5.10 | Load Condition | 21 |
| 3.5.11 | Furnace Atmosphere during TUS | 21 |
| 3.5.12 | Furnace Vacuum Level during TUS | 21 |
| 3.5.13 | Batch Furnaces, Salt Baths, Controlled Temperature Liquid Baths and | |
| | Fluidized Bed Furnaces | 21 |
| 3.5.13.1 | Number of TUS Sensors (also see Table 11) | 21 |
| 3.5.13.2 | Location of TUS Sensors | 21 |
| 3.5.13.3 | TUS Data Collection | 22 |
| 3.5.13.4 | Alternative Probing Method for Salt Baths, Controlled Temperature | |
| | Liquid Baths And Fluidized Bed Furnaces: | 23 |
| 3.5.14 | Continuous and Semi-continuous Furnaces | 23 |
| 3.5.14.1 | Number and Location of TUS Sensors – Volumetric Method | 23 |
| 3.5.14.2 | Number of TUS Sensors – Plane Method | 23 |
| 3.5.14.3 | Location of TUS Sensors – Plane Method | 24 |
| 3.5.14.4 | TUS Data Collection | 24 |
| 3.5.15 | Alternative TUS Methods For Continuous or Semi-continuous Furnaces | |
| | or Furnaces With Retorts or Muffles | 24 |
| 3.5.15.1 | Probing Method | 25 |
| 3.5.15.2 | Property Surveys | 25 |
| 3.5.16 | TUS Sensor Failures | 25 |
| 3.5.17 | TUS Pass/Fail Requirements | 26 |
| 3.5.18 | Relocation of Hot or Cold Recording Sensors for Class A or C | |
| | Instrumentation | 26 |
| 3.5.19 | TUS Failures | 26 |
| 3.5.20 | TUS Instrumentation (also see Tables 1 and 3) | 27 |
| 3.5.21 | TUS Report | 27 |
| 3.5.22 | Prepublication TUS's | 28 |
| 3.5.23 | Radiation Surveys | 28 |
| 3.6 | Laboratory Furnaces | 28 |
| 3.7 | Records | 29 |
| 4.0 | Quality Assurance Provisions | 29 |
| Table 1 | Sensors and Sensor Calibration | 30 |
| Table 2 | Thermocouples and Extension Wire | 31 |
| Table 3 | Instruments and Instrument Calibration | 32 |
| Table 4 | Resolution Requirements for Furnace Chart Recorders | 34 |
| Table 5 | Process Recorder Print and Chart Speeds | 34 |
| | | |