



Standard Specification for Helmets for Non-Motorized Wheeled Vehicle Used by Infants and Toddlers¹

This standard is issued under the fixed designation F 1898; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers performance requirements for helmets manufactured for use by infants and toddlers as passengers or operators of nonmotorized vehicles intended for their use. This specification recognizes the desirability of lightweight construction and ventilation; however, it is a performance standard and is not intended to restrict design.

1.2 All testing and requirements of this specification shall be in accordance with Test Methods F 1446 except as noted.

1.3 *Partial utilization of this standard is prohibited. Any statement of compliance with this specification must be a certification that the product meets all of the requirements of this specification in their entirety. A product that fails to meet any one of the requirements of this specification is considered to have failed this standard, and should not be sold with any indication that it meets parts of this standard.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F 1446 Test Methods for Equipment and Procedures Used in Evaluating the Performance Characteristics of Protective Headgear

3. Labels and Warnings

3.1 In addition to the labeling requirements outlined in Test Methods F 1446, the helmet shall have the words “For use by infants and toddlers when riding non-motorized wheeled vehicles intended for their use” inscribed on one of the interior permanent labels.

¹ This specification is under the jurisdiction of ASTM Committee F08 on Sports Equipment and Facilities and is the direct responsibility of Subcommittee F08.53 on Headgear and Helmets.

Current edition approved May 10, 2001. Published September 2001. Originally published as F 1898 – 98. Last previous edition F 1898 – 00.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

4. Marking the Test Line

4.1 The test line is shown in Fig. 1 and shall be marked in accordance with Test Methods F 1446.

5. Conditioning and Number of Samples

5.1 Four helmets of each model and size are required for testing.

5.2 Conditioning of test samples is described in Sections 11 and 12 of Test Methods F 1446.

6. Headforms

6.1 Headforms to be used in this specification are sizes A and E according to 6.1 of Test Methods F 1446. The appropriate size headform shall be selected (see 3.1.7 of Test Methods F 1446) for the helmet to be tested.

6.2 The weight of the drop assembly as specified in 16.3 of Test Methods F 1446 shall be 3.20 ± 0.15 kg for the A headform and 4.00 ± 0.20 kg for the E headform.

6.3 The headform center of gravity specified in Appendix X1 of Test Methods F 1446 will be allowed an additional tolerance in the X-axis. The tolerance allows the location of the center of gravity to lie between -6.5 mm and 40 mm of the center of the ball socket (positive X is toward the monorail where applicable).

7. Peripheral Vision Requirement

7.1 The peripheral vision requirements shall be as specified in 14.2 of Test Methods F 1446.

8. Retention System Testing

8.1 Retention system tests will be performed before impact testing. The retention system shall be tested in accordance with Test Methods F 1446 using a 7-kg $\pm 5\%$ support assembly.

8.2 The stability (roll-off) test will be performed using a 4-kg drop mass falling a distance of 0.6 m. The stability test will be performed on the ambient helmet.

8.3 The retention system shall remain intact and the helmet must remain on the headform.