

Methods of sampling and test for

Carbonaceous materials used in aluminium manufacture

Part 4. Cold ramming pastes

Section 4.6 Determination of maximum rammed apparent density of unbaked paste

NOTE. It is recommended that this Section be read in conjunction with the general information in BS 6043 : Section 4.0, published separately.

Méthodes d'échantillonnage et d'essai des
matières carbonées utilisées dans la fabrication
de l'aluminium
Partie 4. Pâtes tassées à froid
Section 4.6 Détermination de la masse
volumique apparente maximale des pâtes
brutes tassées

Probenahme und Prüfung kohlenstoffhaltiger
Stoffe für die Aluminiumherstellung
Teil 4. Kaltgerüttelte Pasten
Abschnitt 4.6 Bestimmung der Rütteldichte
ungesinterter Pasten

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Chemicals Standards Policy Committee (CIC/-) to Technical Committee CIC/24, upon which the following bodies were represented:

Aluminium Federation
British Ceramic Research Ltd.
Chemical Industries Association
Institute of Petroleum
Refractories Association of Great Britain

This British Standard, having been prepared under the direction of the Chemicals Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 30 September 1991

© BSI 1991

The following BSI references relate to the work on this standard:
Committee reference CIC/24
Draft for comment 90/54846 DC

ISBN 0 580 19731 X

Amendments issued since publication

Amd. No.	Date	Text affected

Contents

	Page
Committees responsible	Inside front cover
Foreword	2
<hr/>	
Method	
0 Introduction	3
1 Scope	3
2 Principle	3
3 Definition	3
4 Apparatus	3
5 Sampling	3
6 Preparation of test samples	3
7 Procedure	3
8 Calculation and expression of results	5
9 Test report	5
<hr/>	
Figure	
1 Sand rammer	4
