

INTERNATIONAL
STANDARD

ISO/ASTM
51818

Third edition
2013-06-01

**Practice for dosimetry in an electron
beam facility for radiation processing at
energies between 80 and 300 keV**

*Pratique de la dosimétrie dans une installation de traitement par
irradiation utilisant un faisceau d'électrons d'énergies comprises
entre 80 keV et 300 keV*



Reference number
ISO/ASTM 51818:2013(E)

© ISO/ASTM International 2013

ISO/ASTM 51818:2013(E)

© ISO/ASTM International 2013

All rights reserved. Unless otherwise specified no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm without permission in writing from either ISO at the address below or ISO's member body in the country of the requester. In the United States, such requests should be sent to ASTM International.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

ASTM International, 100 Barr Harbor Drive, PO Box C700,
West Conshohocken, PA 19428-2959, USA
Tel. +610 832 9634
Fax +610 832 9635
E-mail khooper@astm.org
Web www.astm.org

Contents

	Page
1 Scope	1
2 Referenced documents	1
3 Terminology	2
4 Significanc and use	2
5 Selection and calibration of the dosimetry system	3
6 Installation and operational qualificatio	3
7 Performance qualificatio	4
8 Routine process control	4
9 Measurement uncertainty	4
10 Documentation	5
11 Keywords	5
Annexes	5
Bibliography	13
Figure A1.1 Example of measurement of dose as function of average beam current I, conveying speed V and beam width W_b. Measured at an electron accelerator with beam energy 110 keV. $K = 216.57 \text{ (kGy} \cdot \text{m}^2\text{) / (A} \cdot \text{s}\text{)}$	6
Figure A1.2 Example of beam width measurement (3 measurements and their average are shown). Beam width was measured on a low energy accelerator installed in an electron beam tunnel for an aseptic fillin line (6)	6
Figure A1.3 Example of beam width measurement at a low-energy electron accelerator facility for curing purpose	7
Figure A1.4 Calculated depth-dose distribution in water (specifi density 1 g cm^{-3})	8
Figure A1.5 Calculated depth-dose distribution in water (specifi density 1 g cm^{-3})	9
Figure A1.6 Methods for measurement of depth dose distribution	9
Figure A1.7 Examples of measurements of depth dose distributions at the same electron beam facility, but at different beam energies	10
Figure A2.1 Average dose measured with three dosimeters (18 μm RCD fil dosimeter; 50 μm RCD fil dosimeter; 130 μm alanine fil dosimeter) all calibrated by irradiation at a 10 MeV electron accelerator, and now irradiated at a 125 keV electron accelerator. Depth dose distribution measured at Risø HDRL 125 keV electron accelerator.	10