



# Standard Specification for Polyester Grade Ethylene Glycol<sup>1</sup>

This standard is issued under the fixed designation E2470; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope\*

1.1 This specification covers polyester grade ethylene glycol.

1.2 The following safety hazards caveat pertains only to the test methods portion, Section 5, described in this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.3 Review the current Materials Safety Data Sheets (MSDS) for detailed information concerning toxicity, first aid procedures, handling and safety precautions.

1.4 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

- D482 Test Method for Ash from Petroleum Products
- D1078 Test Method for Distillation Range of Volatile Organic Liquids
- D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee E15 on Industrial and Specialty Chemicals and is the direct responsibility of Subcommittee E15.02 on Product Standards.

Current edition approved Oct. 1, 2009. Published November 2009. DOI: 10.1520/E2470-09.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

- D1722 Test Method for Water Miscibility of Water-Soluble Solvents
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E202 Test Methods for Analysis of Ethylene Glycols and Propylene Glycols
- E300 Practice for Sampling Industrial Chemicals
- E1064 Test Method for Water in Organic Liquids by Coulometric Karl Fischer Titration
- E1615 Test Method for Iron in Trace Quantities Using the FerroZine Method
- E2193 Test Method for Ultraviolet Transmittance of Monoethylene Glycol (Ultraviolet Spectrophotometric Method)
- E2313 Test Method for Aldehydes in Mono-, Di-, and Triethylene Glycol (Spectrophotometric Method)
- E2409 Test Method for Glycol Impurities in Mono-, Di-, Tri- and Tetraethylene Glycol (Gas Chromatographic Method)
- E2469 Test Method for Chloride in Mono-, Di- and Triethylene Glycol by Ion Chromatography
- E2679 Test Method for Acidity in Mono-, Di-, Tri- and Tetraethylene Glycol by Non-Aqueous Potentiometric Titration
- E2680 Test Method for Appearance of Clear, Transparent Liquids (Visual Inspection Procedure)

## 3. Requirements

3.1 Polyester grade ethylene glycol shall conform to the specification chemical and physical requirements (see Table 1).

## 4. Sampling

4.1 Sample ethylene glycol in accordance with the appropriate sections of Practice E300 for liquid samples.

## 5. Test Methods

5.1 Test each composite sample for chemical and physical requirements using the test methods specified in 3.1. Many of these test methods, along with alternative test methods and

\*A Summary of Changes section appears at the end of this standard.