



Standard Specification for Xylenes for *p*-Xylene Feedstock¹

This standard is issued under the fixed designation D5211; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers xylenes for *p*-xylene feedstock. These xylenes typically are extracted from reformat.

1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or calculated value shall be rounded off “to the nearest unit” in the last right hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as standard. The values given in parentheses are for information only.

1.4 Consult current OSHA regulations, suppliers’ Material Safety Data Sheets (MSDS), and local regulations for all materials used in this specification.

2. Referenced Documents

2.1 *ASTM Standards*:²

D850 Test Method for Distillation of Industrial Aromatic Hydrocarbons and Related Materials

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D3437 Practice for Sampling and Handling Liquid Cyclic Products

D5194 Test Method for Trace Chloride in Liquid Aromatic Hydrocarbons

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

D5808 Test Method for Determining Chloride in Aromatic Hydrocarbons and Related Chemicals by Microcoulometry

D6069 Test Method for Trace Nitrogen in Aromatic Hydrocarbons by Oxidative Combustion and Reduced Pressure Chemiluminescence Detection

D6563 Test Method for Benzene, Toluene, Xylene (BTX) Concentrates Analysis by Gas Chromatography

D7183 Test Method for Determination of Total Sulfur in Aromatic Hydrocarbons and Related Chemicals by Ultraviolet Fluorescence

D7184 Test Method for Ultra Low Nitrogen in Aromatic Hydrocarbons by Oxidative Combustion and Reduced Pressure Chemiluminescence Detection

D7359 Test Method for Total Fluorine, Chlorine and Sulfur in Aromatic Hydrocarbons and Their Mixtures by Oxidative Pyrohydrolytic Combustion followed by Ion Chromatography Detection (Combustion Ion Chromatography-CIC)

D7504 Test Method for Trace Impurities in Monocyclic Aromatic Hydrocarbons by Gas Chromatography and Effective Carbon Number

D7536 Test Method for Chlorine in Aromatics by Monochromatic Wavelength Dispersive X-ray Fluorescence Spectrometry

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 *Other Document*:

OSHA Regulations, 29 CFR paragraphs 1910.1000 and 1910.1200³

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.01 on Benzene, Toluene, Xylenes, Cyclohexane and Their Derivatives.

Current edition approved July 1, 2011. Published September 2011. Originally approved in 1991. Last previous edition approved in 2010 as D5211 – 10. DOI: 10.1520/D5211-11.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.

*A Summary of Changes section appears at the end of this standard.