

BRITISH STANDARD

Specification for belt drives – Endless wedge belts, endless V-belts, banded wedge belts, banded V-belts and their corresponding pulleys

ICS 21.220.10

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2006

ISBN 0 580 48017 8

The following BSI references relate to the work on this standard:

Committee reference MCE/10

Draft for comment 05/30134325 DC

Publication history

First published, September 1964

Second edition, December 1973

Third edition, October 1981

Fourth edition, June 1995

Fifth edition, April 2006

Amendments issued since publication

Amd. no.	Date	Text affected
16655 Corrigendum No. 1	September 2006	Correction to value in Table 2 (spacing for belt section D)

Contents

Foreword *ii*

1	Scope	<i>1</i>
2	Normative references	<i>1</i>
3	Terms and definitions	<i>1</i>
4	Wedge belts, V-belts and banded belts	<i>4</i>
5	Grooved pulleys	<i>9</i>

Annexes

Annex A (normative)	Determination of belt datum length	<i>17</i>
Annex B (informative)	Storage of belts	<i>18</i>
Annex C (informative)	Recommendations for drive design	<i>19</i>
Annex D (normative)	Tests for electrical resistance of belts	<i>27</i>
Annex E (informative)	Recommended practice for installation tension in belt drives and calculation of resultant force imposed on the shaft	<i>29</i>

Bibliography *33*

List of figures

Figure 1	– Belt cross-sections	<i>2</i>
Figure 2	– Basic belt construction	<i>5</i>
Figure 3	– Pulley limiting rotational speed indicating limits for static or dynamic balancing	<i>12</i>
Figure 4	– Multi-groove pulley cross-section	<i>13</i>
Figure A.1	– Measuring pulley and apparatus for measuring belt length	<i>17</i>
Figure C.1	– Selection of wedge belt cross-section	<i>25</i>
Figure C.2	– Selection of V-belt cross-section	<i>26</i>
Figure D.1	– Apparatus for measuring the electrical resistance of belts	<i>28</i>
Figure E.1	– Belt deflection measurement	<i>32</i>

List of tables

Table 1	– Wedge belt and V-belt cross-section dimensions	<i>2</i>
Table 2	– Banded belts – belt spacing	<i>3</i>
Table 3	– Tolerances and force requirements when measuring new belts	<i>6</i>
Table 4	– Dimensions of pulleys for measuring lengths of new belts	<i>6</i>
Table 5	– Nominal datum lengths of wedge belts and V-belts and permitted tolerances	<i>7</i>
Table 6	– Surface finish of pulleys	<i>9</i>
Table 7	– Dimensions of standard grooved pulleys for wedge and V-belt drives	<i>13</i>
Table 8	– Preferred pulley datum diameters	<i>14</i>
Table 9	– Recommended minimum pulley datum diameters	<i>16</i>
Table A.1	– Centre distance variation ΔC on measuring fixture	<i>18</i>
Table C.1	– Service factors for belt drives	<i>23</i>
Table C.2	– Standard base lengths L_o for power rating formulae	<i>24</i>
Table E.1	– Deflection force required for measuring installation tension in wedge and V-belt drives using single or multiple belts	<i>31</i>

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, pages 1 to 33 and a back cover.