

BS 7912:2012



BSI Standards Publication

**Power cables with XLPE  
insulation and metal sheath,  
and their accessories, for  
rated voltages from 66 kV  
( $U_m = 72.5$  kV) to 132 kV  
( $U_m = 145$  kV)  
(Implementation of HD 632)**

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

*raising standards worldwide™*



**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2012

Published by BSI Standards Limited 2012

ISBN 978 0 580 74986 5

ICS 29.060.20

The following BSI references relate to the work on this standard:

Committee reference GEL/20/16

Draft for comment 12/30244367 DC

**Publication history**

First published November 2001

Second (current) edition, December 2012

**Amendments issued since publication**

| Date | Text affected |
|------|---------------|
|------|---------------|

---



**FSC**

**100%**

From well-managed forests

Cert no. SW-COC-004238

[www.fsc.org](http://www.fsc.org)

© 1996 Forest Stewardship Council

## Contents

Foreword *iii*

|    |   |    |
|----|---|----|
| 1  | Scope   | 1  |
| 2  | Normative references  | 1  |
| 3  | Terms and definitions                                       | 2  |
| 4  | Voltage designation and cable design features               | 3  |
| 5  | Marking of cables   | 6  |
| 6  | Cable characteristics                                       | 7  |
| 7  | Accessory characteristics                                   | 7  |
| 8  | Test conditions   | 8  |
| 9  | Routine tests on cables                                     | 8  |
| 10 | Sample tests on cables                                      | 12 |
| 11 | Type tests – Summary  | 16 |
| 12 | Electrical type tests on cables                             | 19 |
| 13 | Type tests on cable components                              | 23 |
| 14 | Longitudinal water penetration type test on complete cables | 28 |
| 15 | Mechanical and thermal type tests on complete cables        | 30 |
| 16 | Type tests on accessories                                   | 35 |
| 17 | Type tests on ancillary equipment                           | 39 |
| 18 | Electrical tests after installation                         | 39 |

### Annexes

|                     |   |    |
|---------------------|---|----|
| Annex A (normative) | Tests and requirements for cable bonding leads            | 45 |
| Annex B (normative) | Tests and requirements for sheath voltage limiters (SVLs) | 49 |
| Annex C (normative) | Tests and requirements for link housings                  | 51 |
| Annex D (normative) | Additional water blocking test for phase conductor        | 54 |

Bibliography 56

### List of figures

|            |  |    |
|------------|--|----|
| Figure 1   | – Shrinkage test   | 28 |
| Figure 2   | – Schematic diagram of apparatus of water penetration test | 29 |
| Figure 3   | – Toothed wheel: 15 teeth                                  | 32 |
| Figure 4   | – Possible arrangement of sample in saline bath            | 33 |
| Figure D.1 | – Apparatus for water penetration test                     | 55 |

### List of tables

|          |   |    |
|----------|---|----|
| Table 1  | – Test voltages   | 4  |
| Table 2  | – Cable maximum temperatures  | 5  |
| Table 3  | – Number of samples for sample tests  | 12 |
| Table 4  | – Test conditions and requirements for particular characteristics of cable insulating materials             | 13 |
| Table 5  | – Type tests on cable components  | 19 |
| Table 6  | – $\tan \delta$ in relation to voltage  | 21 |
| Table 7  | – Power frequency voltage test  | 22 |
| Table 8  | – Tests and requirements for mechanical characteristics of XLPE insulating material before and after ageing | 24 |
| Table 9  | – Test requirements for particular characteristics of oversheathing for cables                              | 25 |
| Table 10 | – Lightning impulse voltage test levels   | 38 |
| Table 11 | – A.C. test voltages  | 40 |
| Table 12 | – Maximum contact resistance values   | 40 |
| Table 13 | – Voltage and current range for maintenance test on silicon carbide units                                   | 44 |