

INTERNATIONAL STANDARD

ISO/IEC 12248

First edition
1993-12-15

Information technology — 3,81 mm wide magnetic tape cartridge for information interchange — Helical scan recording — DATA/DAT-DC format using 60 m and 90 m length tapes

*Technologies de l'information — Cartouche de bande magnétique de
3,81 mm de large pour l'échange d'information — Enregistrement par
balayage en spirale — Format DATA/DAT-DC utilisant des bandes
de 60 m et 90 m de long*

Adopted by INCITS (InterNational Committee for Information Technology Standards) as an American National Standard.

Date of ANSI Approval: 5/12/98

Published by American National Standards Institute,
25 West 43rd Street, New York, New York 10036

Copyright 2002 by Information Technology Industry Council (ITI).
All rights reserved.

These materials are subject to copyright claims of International Standardization Organization (ISO), International Electrotechnical Commission (IEC), American National Standards Institute (ANSI), and Information Technology Industry Council (ITI). Not for resale. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ITI. All requests pertaining to this standard should be submitted to ITI, 1250 Eye Street NW, Washington, DC 20005.

Printed in the United States of America



Reference number
ISO/IEC 12248:1993(E)

Contents	Page
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridge	1
2.2 Generating system	1
2.3 Receiving system	1
3 Normative references	1
4 Definitions	2
4.1 Absolute Frame Number (AFN)	2
4.2 algorithm	2
4.3 Area ID	2
4.4 Automatic Track Finding (ATF)	2
4.5 Average Signal Amplitude	2
4.6 azimuth	2
4.7 back surface	2
4.8 byte	2
4.9 cartridge	2
4.10 Channel Bit	2
4.11 Codeword	2
4.12 Data Format ID	2
4.13 End of Data (EOD)	2
4.14 End of Information (EOI)	2
4.15 End of Partition (EOP)	2
4.16 entity	2
4.17 Error Correcting Code (ECC)	2
4.18 flux transition position	2
4.19 flux transition spacing	2
4.20 frame	2
4.21 group	2
4.22 Logical Beginning of Tape (LBOT)	2

© ISO/IEC 1993

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

4.23	Logical End of Tape (LEOT)	2
4.24	magnetic tape	3
4.25	master reference	3
4.26	Master Standard Amplitude Calibration Tape	3
4.27	Master Standard Reference Tape	3
4.28	Optimum Recording Field	3
4.29	partition	3
4.30	partition reference	3
4.31	Physical Beginning of Tape (PBOT)	3
4.32	Physical End of Tape (PEOT)	3
4.33	physical recording density	3
4.34	pre-recording condition	3
4.35	processed record	3
4.36	processed record sequence	3
4.37	processing	3
4.38	record	3
4.39	Reference Recording Field	3
4.40	Secondary Standard Amplitude Calibration Tape	3
4.41	Secondary Standard Reference Tape	3
4.42	Separator Mark	3
4.43	Standard Reference Amplitude	4
4.44	tape noise amplitude	4
4.45	Tape Reference Edge	4
4.46	track	4
5	Environment and safety	4
5.1	Testing environment	4
5.2	Operating environment	4
5.3	Storage environment	4
5.4	Transportation	4
5.5	Safety	5
5.6	Flammability	5
Section 2 - Requirements for the case		5
6	Dimensional and mechanical characteristics of the case	5
6.1	General	5
6.2	Overall dimensions	5
6.3	Loading grip	6
6.4	Holding areas	6
6.5	Notches of the lid	6
6.6	Lid dimensions	6
6.7	Optical detection of the beginning and end of tape	7
6.8	Bottom side	8
6.8.1	Locking mechanism of the slider	8
6.8.2	Access holes	9
6.8.3	Recognition, sub-datum and write-inhibit holes	9
6.8.4	Datum holes	10
6.8.5	Access room for tape guides	11
6.8.6	Holes for accessing the hubs	11