



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.961

(03/93)

DIGITAL SECTIONS AND DIGITAL LINE SYSTEMS

**DIGITAL TRANSMISSION SYSTEM ON
METALLIC LOCAL LINES FOR ISDN
BASIC RATE ACCESS**

ITU-T Recommendation G.961

(Previously "CCITT Recommendation")

FOREWORD

The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the International Telecommunication Union. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, established the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

ITU-T Recommendation G.961 was revised by the ITU-T Study Group XVIII (1988-1993) and was approved by the WTSC (Helsinki, March 1-12, 1993).

NOTES

1 As a consequence of a reform process within the International Telecommunication Union (ITU), the CCITT ceased to exist as of 28 February 1993. In its place, the ITU Telecommunication Standardization Sector (ITU-T) was created as of 1 March 1993. Similarly, in this reform process, the CCIR and the IFRB have been replaced by the Radiocommunication Sector.

In order not to delay publication of this Recommendation, no change has been made in the text to references containing the acronyms "CCITT, CCIR or IFRB" or their associated entities such as Plenary Assembly, Secretariat, etc. Future editions of this Recommendation will contain the proper terminology related to the new ITU structure.

2 In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

		<i>Page</i>
1	General	1
	1.1 Scope	1
	1.2 Definition	1
	1.3 Objectives	2
	1.4 Abbreviations	2
2	Functions	3
	2.1 B-channel	3
	2.2 D-channel	3
	2.3 Bit timing	3
	2.4 Octet timing	3
	2.5 Frame alignment	4
	2.6 Activation from LT or NT1	4
	2.7 Deactivation	4
	2.8 Power feeding	4
	2.9 Operations and maintenance	4
3	Transmission medium	4
	3.1 Description	4
	3.2 Minimum ISDN requirements	5
	3.3 DLL physical characteristics	5
	3.4 DLL electrical characteristics	5
4	System performance	8
	4.1 Performance requirements	8
	4.2 Performance measurements	8
5	Transmission method	13
6	Activation/deactivation	14
	6.1 General	14
	6.2 Physical representation of signals	14
7	Operation and maintenance	14
	7.1 Operation and maintenance functions	14
	7.2 C _L channel	14
	7.3 Transfer mode of operation and maintenance links	14
8	Power feeding	15
	8.1 General	15
	8.2 Power feeding options	15
	8.3 Power feeding and recovery methods	15
	8.4 DLL resistance	15
	8.5 Wetting current	15
	8.6 LT aspects	17
	8.7 Power requirements of NT1 and regenerator	17
	8.8 Current transient limitation	17
9	Environmental conditions	17
	9.1 Climatic conditions	17
	9.2 Protection	17
	9.3 Electromagnetic compatibility	18
	Appendix I – Electrical characteristics of an MMS 43 transmission system	18
	I.1 Line code	18
	I.2 Symbol rate	19