

INTERNATIONAL TELECOMMUNICATION UNION





TELECOMMUNICATION STANDARDIZATION SECTOR OF ITU

SERIES Q: SWITCHING AND SIGNALLING Q3 interface

CORBA-based TMN performance management service

ITU-T Recommendation Q.822.1

ITU-T Q-SERIES RECOMMENDATIONS SWITCHING AND SIGNALLING

	·····
SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4-Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60-Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100-Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5	Q.120-Q.249
SPECIFICATIONS OF SIGNALLING SYSTEM No. 6	Q.250-Q.309
SPECIFICATIONS OF SIGNALLING SYSTEM R1	Q.310-Q.399
SPECIFICATIONS OF SIGNALLING SYSTEM R2	Q.400-Q.499
DIGITAL EXCHANGES	Q.500-Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600-Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700-Q.799
General	Q.700
Message transfer part (MTP)	Q.701–Q.709
Signalling connection control part (SCCP)	Q.711–Q.719
Telephone user part (TUP)	Q.720-Q.729
ISDN supplementary services	Q.730–Q.739
Data user part	Q.740-Q.749
Signalling System No. 7 management	Q.750-Q.759
ISDN user part	Q.760-Q.769
Transaction capabilities application part	Q.770–Q.779
Test specification	Q.780–Q.799
Q3 INTERFACE	Q.800-Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
General	Q.850–Q.919
Data link layer	Q.920–Q.929
Network layer	Q.930–Q.939
User-network management	Q.940–Q.949
Stage 3 description for supplementary services using DSS1	Q.950–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000-Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700-Q.1799
SPECIFICATIONS OF SIGNALLING RELATED TO BEARER INDEPENDENT CALL CONTROL (BICC)	Q.1900–Q.1999
BROADBAND ISDN	Q.2000–Q.2999

For further details, please refer to the list of ITU-T Recommendations.

CORBA-based TMN performance management service

Summary

This Recommendation defines an information model to be used in telecommunications performance management (PM) based on CORBA. It defines in Interface Definition Language (IDL) a set of interfaces, notifications, and constants. The intent of this Recommendation is to define a CORBA/IDL model similar to that defined in ITU-T Recs. X.739 and Q.822 using CMISE. This Recommendation is compliant with CORBA modelling standards in ITU-T X.780, X.780.1, Q.816, Q.816.1 and M.3120.

Source

ITU-T Recommendation Q.822.1 was prepared by ITU-T Study Group 4 (2001-2004) and approved under the WTSA Resolution 1 procedure on 7 October 2001.