



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

G.165

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

(03/93)

**GENERAL CHARACTERISTICS
OF INTERNATIONAL TELEPHONE CONNECTIONS
AND INTERNATIONAL TELEPHONE CIRCUITS**

ECHO CANCELLERS

ITU-T Recommendation G.165

(Previously "CCITT Recommendation")

FOREWORD

The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the International Telecommunication Union. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, established the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

ITU-T Recommendation G.165 was revised by the ITU-T Study Group XV (1988-1993) and was approved by the WTSC (Helsinki, March 1-12, 1993).

NOTES

1 As a consequence of a reform process within the International Telecommunication Union (ITU), the CCITT ceased to exist as of 28 February 1993. In its place, the ITU Telecommunication Standardization Sector (ITU-T) was created as of 1 March 1993. Similarly, in this reform process, the CCIR and the IFRB have been replaced by the Radiocommunication Sector.

In order not to delay publication of this Recommendation, no change has been made in the text to references containing the acronyms "CCITT, CCIR or IFRB" or their associated entities such as Plenary Assembly, Secretariat, etc. Future editions of this Recommendation will contain the proper terminology related to the new ITU structure.

2 In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

CONTENTS

| | <i>Page</i> |
|--|-------------|
| 1 General | 1 |
| 2 Definitions relating to echo cancellers | 3 |
| 2.1 echo canceller | 3 |
| 2.2 echo loss (A_{ECHO}) | 3 |
| 2.3 pure delay (t_r) | 3 |
| 2.4 (near-end) echo path or end delay (t_d) | 4 |
| 2.5 cancellation (A_{CANC}) | 4 |
| 2.6 residual echo level (L_{RES}) | 4 |
| 2.7 nonlinear processor (NLP) | 4 |
| 2.8 nonlinear processing loss (A_{NLP}) | 4 |
| 2.9 returned echo level (L_{RET}) | 5 |
| 2.10 combined loss (A_{COM}) | 5 |
| 2.11 convergence | 5 |
| 2.12 convergence time | 5 |
| 2.13 leak time | 5 |
| 3 Characteristics of echo cancellers | 5 |
| 3.1 General | 5 |
| 3.2 Purpose, operation and environment | 6 |
| 3.3 External enabling/disabling | 8 |
| 3.4 Tests and requirements for performance with inputs signals applied to the send and receive paths | 8 |
| 4 Characteristics of an echo canceller tone disabler | 16 |
| 4.1 General | 16 |
| 4.2 Disabler characteristics | 16 |
| 4.3 Guardband characteristics | 16 |
| 4.4 Holding-band characteristics | 17 |
| 4.5 Operate time | 17 |
| 4.6 False operation due to speech currents | 17 |
| 4.7 False operation due to data signals | 17 |
| 4.8 Release time | 17 |
| 4.9 Other considerations | 17 |
| 5 Nonlinear processors for use in echo cancellers | 17 |
| 5.1 Scope | 17 |
| 5.2 General principles and guidelines | 18 |
| Annex A – Echo cancellers without nonlinear processing | 21 |
| Annex B – Description of an echo canceller reference tone disabler | 22 |
| B.1 General | 22 |
| B.2 Disabler characteristics | 22 |
| B.3 Guardband characteristics | 22 |
| B.4 Holding-band characteristics | 22 |
| B.5 Operate time | 22 |
| B.6 False operation due to speech currents | 22 |
| B.7 False operation due to data signals | 23 |
| B.8 Release time | 23 |