

**AEROSPACE
RECOMMENDED
PRACTICE**

SAE ARP4163

Issued 2003-10

Balancing Machines: Tooling Design Criteria

FOREWORD

Tooling for balancing machines is a complex subject with many requirements that have been developed over a considerable period of time. The definition of balancing tooling covers a wide range of items from drive shafts and bearings to complete fixtures for locating engine modules.

This document was prepared by the SAE EG-1A committee, it supersedes ARP1382.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2003 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)

Tel: 724-776-4970 (outside USA)

Fax: 724-776-0790

Email: custsvc@sae.org

<http://www.sae.org>

SAE WFR ADDRESS:

Copyright SAE International

Provided by IHS under license with SAE

No reproduction or networking permitted without license from IHS

Not for Resale

SAE ARP4163

TABLE OF CONTENTS

1.	SCOPE	5
1.1	Purpose.....	5
1.2	Equipment Selection for Specific Applications	5
2.	APPLICABLE DOCUMENTS	5
2.1	SAE Publications.....	6
3.	METHODS OF ROTOR SUPPORT IN A HORIZONTAL BALANCING MACHINE.....	6
3.1	Twin-Roller Bearings.....	6
3.2	V-type Bearings.....	7
3.3	Engine Bearings.....	7
3.4	Slave Bearings	8
3.5	Slave Races	8
3.6	Sleeve Bearings	8
3.7	Swivel Bearing Bridges	9
3.8	Negative Load Devices	9
3.8.1	Purpose.....	9
3.8.2	Types of Negative Load Devices	10
3.9	Axial Thrust Stops (End Stops, Thrust Arrestors)	10
3.9.1	Purpose.....	10
3.9.2	Mounting of Axial Thrust Stops	10
3.9.3	Types of Axial Thrust Stops	11
4.	CRADLES, STATOR TOOLING, AND TIEBARS	11
4.1	Purpose.....	11
4.2	Design Prerequisites	12
4.3	Machine and Rotor Interface	12
4.4	Engine Stators: Assembly Balancing	13
4.5	Tie Bars.....	13
4.5.1	Use of Rollers With Tie Bars	14
5.	DRIVE TOOLING - DIRECT AND BELT	14
5.1	General Design	14
5.2	Balancing	15
5.3	Material	15
5.4	Mounting Interface	15
5.5	Rotor Connection	15
5.6	Rotation Direction.....	16
5.7	End-Drive Interface Dimensions	16
5.8	Belt - Drive Pulley Interface.....	17
5.8.1	Pulley Mounting Location	17

SAE ARP4163

TABLE OF CONTENTS (CONTINUED)

5.8.2	Drive Surface	17
5.9	Drive Adapter Assemblies - Balancing, and Unbalance Error Introduced.....	17
5.9.1	Balancing an End Drive Adapter as Separate Entity.....	17
5.9.2	Balancing an End-Drive U-joint Drive Shaft and Adapter While Assembled to a Rotor	18
5.9.3	Balancing a Belt-Drive Pulley While Assembled to a Rotor	18
5.9.4	Alternate Method for Balancing an Adapter or Pulley While Assembled to a Rotor	18
6.	BALANCING ARBORS FOR HORIZONTAL BALANCING MACHINES.....	19
6.1	General Design and Purpose.....	19
6.2	Construction	19
6.3	Arbor With Journals.....	19
6.4	Arbor With Bearings	19
6.5	Cartridge Type Arbor.....	20
6.6	Correction Planes.....	20
6.7	Maintenance.....	20
6.8	Loading	20
6.9	Loading Support.....	21
6.10	Rotor Removal	21
6.11	Rotor Location.....	21
6.12	Rotor Angular Location	21
6.13	Removable Parts.....	21
7.	ADAPTERS FOR VERTICAL BALANCING MACHINES.....	21
7.1	General Design and Purpose.....	21
7.2	Rotor Location	22
7.3	Rotor Clamping	22
7.4	Arbor Balance	22
7.5	Torque Transmission	22
7.6	Rotation Direction.....	22
7.7	Concentricity	22
7.8	Tooling Repeatability.....	22
7.9	Runout Compensation	23
7.10	Rotor Centering.....	23
8.	BALANCE	23
8.1	Arbor Balance	23
8.2	Index Balancing.....	23
8.3	Runout Compensation	24
8.4	Index Check	24