

INTERNATIONAL STANDARD

ISO
7299

Second edition
1996-05-15

Diesel engines — End-mounting flanges for fuel injection pumps

*Moteurs diesels — Brides de montage des pompes d'injection de
carburant*



Reference number
ISO 7299:1996(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 7299 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 7, *Injection equipment and filters for use on road vehicles*.

This second edition cancels and replaces the first edition (ISO 7299:1984), which has been technically revised with the addition of type 9 flanges.

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Diesel engines — End-mounting flanges for fuel injection pumps

1 Scope

This International Standard specifies dimensional requirements for:

- a) four types of end-mounting flange for rotary and distributor fuel injection pumps,
- b) five types of end-mounting flange for in-line fuel injection pumps,

for use in diesel (compression-ignition) engines.

2 Dimensions and tolerances

2.1 General

Engine manufacturers are encouraged to use the tolerance H8 for the female register diameter.

If functionally necessary, the tolerance g8 on the pump spigot diameter ($\varnothing d_1$ in the figures) may be replaced by f7, and the tolerance H8 on the female register diameter may be replaced by H7, by mutual agreement between supplier and user.

NOTES

- 1 The diameter d_2 in the figures and tables corresponds to the diameter d specified in ISO 6519:1993, *Diesel engines — Fuel injection pumps — Tapers for shaft ends and hubs*.

- 2 In the case of in-line fuel injection pumps, the flange configuration can optionally be rotated relative to the pump housing.

2.2 Rotary and distributor fuel injection pumps

2.2.1 Type 1 flange

See figure 1 and table 1.

2.2.2 Type 2 flange

See figure 2 and table 2.

2.2.3 Type 3 flange

See figure 3 and table 3.

2.2.4 Type 9 flange

See figure 4 and table 4.

2.3 In-line fuel injection pumps

2.3.1 Type 4 flange

See figure 5 and table 5.