


- 1. FOR PART NUMBERS AS3120-15 THRU AS3100-17 THE THREAD PD SHALL REPLACE DATUM B
- 2. MATERIAL: CORROSION RESISTANT STREE AMS 5731.
- 3. MANUPACTURING SPECIFICATION: AMS 7477.
- FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
- SURFACE TEXTURE: ANSI B46.1-1962: UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES, (3.2 MICROMETRES) EXCEPT UPSET HEAD.
- 6. BREAK SHARP EDGES ,003-,015 (0.08-0.38) UNLESS OTHERWISE SPECIFIED.
- 7. DIMENSIONS IN INCHES (MILLIMETRES). METRIC CONVERSIONS ARE INTERNATIONAL SYSTEM UNITS (S1). UNLESS OTHERWISE SPECIFIED, TOLERANCES: ANGULAR DIMENSIONS ±5°.
- 8. DIMENSIONS AND TOLERANCING: ANSI Y14.5-1973.
- 9. DO NOT USE UNASSIGNED PART NUMBERS.



REAFFIRMED 2004-02

1979-07

CUSTODIAN: SAE E-25



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, DRILLED 6 HOLES, PD SHANK, CRES AMS 5731, .5625-18 UNJF-3A

AS3120 SHEET 1 OF 2

Copyright 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.