

Socket Wrenches, Hand (Metric)

1. SCOPE:

This SAE Aerospace Standard covers high strength commercial sockets and universal sockets which possess the strength, clearances, and internal wrenching design so configured that, when mated with hexagon (6 point) fasteners, they shall transmit torque to the fastener without bearing on the outer 5% of the fastener's wrenching points. This document provides additional requirements beyond ANSI B107.5 appropriate for aerospace use.

Inclusion of dimensional data in this document is not intended to imply all of the products described therein are stock production sizes. Consumers are requested to consult with manufacturers concerning lists of stock production sizes.

1.1 Classification:

Sockets and universal sockets covered by this document shall be of the following classes and styles as specified:

- a. Class 1 - Sockets, double hexagon (12 point)
 - (1) Style A - Regular length
 - (2) Style B - Long length
 - (3) Style C - Mid length
- b. Class 3 - Universal sockets, double hexagon (12 point)

2. APPLICABLE DOCUMENTS:

2.1 The following documents of the issue in effect on the date of invitations for bid or request for proposal form a part of this document to the extent specified herein.

2.1.1 SAE Publications: Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

AS478	Identification - Marking Methods
MA1547	Wrench, Twelve Spline, Metric

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: custsvc@sae.org
<http://www.sae.org>

SAE MA4534

2.1.2 ASTM Publications: Available from American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

- ASTM A 754 Coating Thickness by X-ray Fluorescence, Standard Test Method for
- ASTM B 487 Measurement of Metal and Oxide Coating Thickness, Examination of a Cross Section
- ASTM B 499 Measurement of Coating Thickness by the Magnetic Method, Standard Test Method for
- ASTM B 504 Measurement of Thickness of Metallic Coatings by the Coulometric Method, Standard Test Method for
- ASTM B 530 Measurement of Coating Thickness by the Magnetic Method: Electrodeposited Nickel Coatings of Magnetic and Nonmagnetic Substrates, Standard Test Method for
- ASTM B 568 Measurement of Coating Thickness by X-ray Spectrometry, Standard Test Method for
- ASTM B 571 Adhesion of Metallic Coatings, Standard Test Methods for
- ASTM B 748 Measurement of Thickness of Metallic Coatings by Measurement of Cross Section with a Scanning Electron Microscope, Standard Test Method for

2.1.3 ANSI Publications: Available from American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

ANSI B107.5 Sockets Wrenches, Hand (Metric Series)

3. REQUIREMENTS:

3.1 General:

Unless otherwise specified herein, all dimensions and attributes shall be in conformance with ANSI B107.5.

3.2 Materials:

The materials used in the manufacture of the sockets and universal sockets shall be steel, the chemical composition and heat treatment of which shall be such as to produce tools conforming to the physical requirements specified herein. Failure under load shall not result in fragmentation of the socket. Powdered metal or cast steel shall not be used.

3.3 Marking:

The sockets shall be marked in a permanent manner with the country of origin and the manufacturer's name, or with a trademark of such known character that the source of manufacture may be readily determined. In addition, the tools shall be marked in a permanent manner with the nominal wrench opening. Marking methods shall be in accordance with AS478.

SAE MA4534

3.4 Hardness:

Sockets shall be heat treated to a hardness of 40 to 54 Rockwell C.

3.5 Test Loads:

When tested as specified, sockets shall withstand the applicable cyclic and proof test loads specified in Table 1 and Table 2 without failure or permanent deformation (set) which might affect the durability or serviceability of the sockets.

**TABLE 1 - Class 1, Socket, Test Loads by SQ DR Size
(Torque in Newton-Meters)**

Size	1/4 Proof	1/4 Cyclic	3/8 Proof	3/8 Cyclic	1/2 Proof	1/2 Cyclic	3/4 Proof	3/4 Cyclic
5	17	12						
5.5	22	15						
6	28	20	28	20				
7	42	29	42	29				
8	58	41	62	43				
9	70	49	89	62				
10	70	49	120	84	155	108		
11	70	49	155	108	195	136		
12	70	49	205	144	240	168		
13	70	49	260	182	295	206		
14	70	49	280	196	350	245		
15			280	196	420	294		
16			280	196	485	340		
17			280	196	560	392		
18			280	196	680	476		
19			280	196	680	476		
20			280	196	680	476		
21			280	196	680	476		
22			280	196	680	476	1530	1070
23					680	476	1670	1170
24					680	476	1800	1260
25					680	476	1955	1370
26					680	476	2030	1420
27					680	476	2030	1420
28					680	476	2030	1420
30					680	476	2030	1420
32					680	476	2030	1420
34							2030	1420
36							2030	1420
41							2030	1420
46							2030	1420
50							2030	1420
55							2030	1420
60							2030	1420